

Mixagem de áudio e Gerenciamento

**Audio Delay Box****AD-10**

|                       |   |
|-----------------------|---|
| Audio Input           | 1 x 3.5mm Jack Socket<br>( Tip: Mic/Line (Left) □ Ring: Mic/Line (Right) □ Sleeve: GND)<br>16K ohms, MAX Line input Level: +10dBV                       |
| Audio Output          | 2 x unbalanced stereo audio, RCA sockets 600 ohms, MAX=+10dBV   |
| Audio Indicator       | 2 Rows (Left / Right)   |
| Audio Delay           | Up to 400ms   |
| Audio Sample Rates    | 48 KHz  |
| Special Feature       | Switchable for Microphone input or Audio Line input<br>Switchable Condenser / Dynamic Microphone<br>Stereo RCA output connectors for wide compatibility |
| Chassis               | Compact and lightweight design  |
| Power                 | USB Type C (5V/1A) - Not included with the product. A generic USB-C to USB cable can be used to power the unit.   |
| Dimension (LxWxH)     | 151 x 88.5 x 30.7 mm  |
| Weight                | 0.18 kg   |
| Operating Temp. Range | 0~40 °C   |
| What's in the Box     | 1 x AD-10 product<br>1 x RCA to 3.5mm Cable   |