

Monitores LCD

**4K Monitor de produção ScopeView 17"****TLM-170KM**

|                             |   |
|-----------------------------|---|
| Screen                      | 17.3" LED Backlit   |
| Chassis                     | Pull-Out  |
| Resolution                  | 3840 × 2160   |
| Viewing Angle               | (H) +89/-89°<br>(V) +89/-89°  |
| Luminance/Contrast          | 300cd/m <sup>2</sup><br>1000:1  |
| Video Inputs                | 1 x 12G SDI<br>2 x HDMI (2.0)   |
| Loop Through                | 1 x 12G SDI<br>1 x HDMI (2.0)   |
| Supported Input Resolutions | SDI:<br>4096x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>3840x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>4096x2160Psf (23.98/24/25/29.97/30)<br>3840x2160Psf (23.98/24/25/29.97/30)<br>1920x1080p (23.98/24/25/29.97/30/50/59.94/60)<br>1920x1080i (50/59.94/60)<br>1920x1080Psf (23.98/24/25/29.97/30)<br>1280×720p (23.98/24/25/29.97/30/50/59.94/60)<br>525i, 625i<br>HDMI:<br>4096x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>3840x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>1920x1080p (23.98/24/25/29.97/30/50/59.94/60)<br>1920x1080i (50/59.94/60)<br>1280×720p (23.98/24/25/29.97/30/50/59.94/60)<br>720 x480i (NTSC), 720 x576i (PAL)<br>640 x800, 800 x600, 1024 x768, 1280 x800 |
| Aspect Ratio                | 16:9, 4:3   |
| Aspect Marker               | YES   |
| Safety Marker               | YES   |
| Tally LED                   | Live (Red)<br>Cued (Green)  |
| Audio In/Out                | Input: Embedded Audio (48KHz sampling)<br>Output: Analog stereo (Phone Jack)<br>Speaker x 2 (3W)  |

|                       |  |
|-----------------------|--|
| Special Features      | <p>waveform,<br/>vector scope,<br/>Focus Peaking,<br/>False Color,<br/>Exposure (Zebras),<br/>Histogram,<br/>HDR / SDR,<br/>Time Code,<br/>Audio Vector,<br/>Camera Log,<br/>Gamma, Marker,<br/>Pixel to Pixel,<br/>Zoom,<br/>H/V Delay,<br/>DSLR,<br/>Freeze,<br/>Image Flip,<br/>Check Field,<br/>Level Meter,<br/>Color Bar,<br/>Color Calibration.</p> |
| Dimension (WxHxD)     | 403 x 305 x 37 mm  |
| Weight                | 5.2kg  |
| Operating Temp. Range | 0~40 °C  |
| Power                 | DC 12V, 40.1W  |
| What's in the Box     | <p>1 x TLM-170KM product<br/>1 x AD Switch DC 12V<br/>4 x Screw <math>\phi</math>4.0*6m/m<br/>8 x Screw <math>\phi</math>3.0*6m/m<br/>8 x Screw M5 x 10mm<br/>5 x Cable tie</p>  |