

# Datavideo Product Compare

<https://datavideo.com.br/>

Número do modelo	<b>ITC-100</b>
Product	<b>Sistema de Intercom</b>
Tally	2 x 15 Pin DSub Sockets for Tally A and B
MIC / Headset	3.5 mm Stereo Jack Socket for Headphone / Microphone combination Headset Impedance 8-600 Ohms 100 mW (min)
Headphone	¼" (6.3mm) Stereo Headphone Socket Headset Impedance 8-600 Ohms 100 mW (min)
Light Socket (DC 12 V)	3 PIN XLR Connector PIN 2: 12V PIN 3: GND Light Power Consumption: 12 V / 100 mA (MAX.)
Microphone	3 PIN XLR / ¼" (6.3mm) Jack Microphone Socket Switchable Condenser / Dynamic Input Microphone Level -67 dB
Frequency Response	550-3.6 kHz, <+/- 3dB
THD	< 3%
S/N	> 50dB
Built-in Speaker	70mm x 30mm 32 Ohm 3 Watts
Operating Range	Up to 200 meters between base station and slave
Operating Temp. Range	0~40 °C

Dimension (LxWxH)	482 x 127 x 46 mm
Weight	1.9 kg
Power	DC 12V, 8W
What's in the Box	<ul style="list-style-type: none"> <li>1 x ITC-100 Base Unit</li> <li>4 x ITC-100SL Belt Pack</li> <li>4 x ITC-100SL Carry Case</li> <li>4 x Cable 5pin XLR to XLR</li> <li>4 x 3.5mm Jack to 3.5mm Jack Cable</li> <li>4 x Headset with microphone</li> <li>4 x Tally LED Indicator</li> <li>1 x XLR Gooseneck Microphone</li> <li>1 x XLR Gooseneck Light</li> <li>1 x 12V 1A Power Supply Unit</li> </ul>