

HDBaseT

4K HDBaseT Receiver Box**HBT-16**

| | |
|------------------------|--|
| Video/Audio Input | HDBaseT RJ-45 x1 |
| Video/Audio Output | HDMI 2.0 x1 |
| Supported Video Format | 2160p: 60/59.94/50/30/29.97/25 1080p: 60/59.94/50/30/29.97/25 1080i: 60/59.94/50 720p: 60/59.94/50 480i: 59.94 576i: 50 |
| Video Process | 4K2K60 4:4:4 8bits 4K2K60 4:2:0 10bits |
| Video bandwidth | Single-link 600MHz [18Gbps] |
| DVIP | RJ-45 x1(input) |
| RS-422/ RS-232 | RJ-45 x1 |
| Power | DC IN: DC 56V |
| PoE Output | 65W |
| HDBaseT Distance | 2160p60/59.94/50 Up to 100m by CAT. 6A Cable (Resolution downward supported) |
| HDMI compliance | HDMI 2.0 |
| HDCP compliance | HDCP 2.2/1.4 (Bypass) |
| Audio support | Surround sound (up to 7.1ch) |
| Dimension (LxWxH) | 157 x 85 x 46mm |
| Weight | 450 g |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x HBT-16 main unit 1 x AC cord 1 x DC 56V power adaptor |