

4K Virtual Multicam Switcher

4K-Mehrkanal-Touchscreen-Umschalter für „Region of Interest“

KMU-200

| | |
|---------------------------------|--|
| Video Standard | UHD & HD |
| Video Format | Input: 3840x2160p 23.98/24/25/29.97/30/50/59.94/60 1080p 50/59.94/60 Output: 1080p 50/59.94/60 720p 50/59.94/60 |
| Video Format | 4:4:4 / 4:2:2 / 4:2:0 |
| Video Input | 1x HDMI 2.0 1x HDMI 1.4 with Loop through |
| Video Output | 2x HDMI 1.4 |
| Support Video Output Resolution | 1920 x 1080p 50/59.94/60 1280 x 720p 50/59.94/60 |
| Multiview Out | --- |
| Multiview Mode | --- |

Streaming

| | |
|---------------------------|---|
| Streaming Encode | H.264/AVC, Main/High Profile |
| Streaming Video Bitrate | Record Only: Up to 16Mbps (1080p50/60) Stream Only: Up to 10Mbps (1080p50/60), dual stream Record+Stream: 36Mbps (1080p50/60) |
| Streaming Video Rate Mode | CBR |
| Streaming Audio Mode | Stereo/Mono |
| Streaming Audio Bitrate | Stereo: 64~384Kbps Mono: 32~192Kbps |
| Streaming Protocols | TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT |
| Network Interface | 1x RJ45 (10/100Mbps Ethernet) |

Recording

| | |
|-------------------------------|--------------------------|
| Recording Storage Medium | SD Card (Class 10 above) |
| Recording Storage File System | NTFS, FAT, exFAT |
| Recorded File Format | MP4 |
| Built-in Audio Mixer | Yes, 4 channels |

Audio

| | |
|-----------------|-----------------------|
| Audio Input | 2x XLR(Mic) 2x RCA |
| Audio Output | 2x Unbalanced RCA |
| Audio Sampling | --- |
| Reference Input | --- |

Others

| | |
|-----------------------|--|
| Control Interface | --- |
| Preview Display | 14" Capacitive Touch LCD |
| Controller | --- |
| Dimension (LxWxH) | 438 x 331 x 114 mm |
| Weight | 4.3 kg |
| Power Supply | DC 12V, 52W |
| Operating Temp. Range | 0~40 °C |
| What's in the box | 1 x KMU-200 Main Unit 1 x AD Switch DC 12V with AC Cord |