

# Datavideo Product Compare

<https://datavideo.com./de/>

|                            |  |
|----------------------------|--|
| Modell-Nr                  | <b>HS-2600</b>   |
| Product                    | <b>HD 8-Channel HD Portable Video Streaming Studio</b>   |
| Video Standard             | HD   |
| Video Format               | 1080p 50/ 59.94/ 60Hz<br>1080i 50/ 59.94/ 60Hz<br>720p 50/ 59.94/ 60Hz                               |
| Input Rutable / Crosspoint | All 8, repeatable  |
| Video Input                | 4 x 3G-SDI<br>4 x HDMI   |
| Computer Graphic Interface | 4 via HDMI   |
| Down-converted Output      | -----  |
| Video Output               | 3 x 3G-SDI for PGM (AUX assignable)<br>1 x HDMI 1.4 for PGM (AUX assignable)<br>3 x HDMI 1.4 for PGM |
| Analogue Audio Input       | 2 x XLR/MIC (6.3mm) Combo Socket<br>1 x stereo RCA audio   |
| Analogue Audio Output      | 1 x stereo RCA audio   |

|                                |  |
|--------------------------------|--|
| Digital Embedded Audio Support | SDI Input/Output 4 channels,<br>HDMI Input/Output 2 channels |
| Audio Delay Calibration        | Up to 16 frames  |
| A+V Switching                  | Yes  |
| USK                            | 4  |
| DSK                            | 2  |
| Picture in Picture             | 4  |
| Logo Insertion                 | 2  |
| Title Creator                  | Yes  |
| Built-in Audio Mixer           | ----   |
| Built-in Monitor Display       | 17.3" HD TFT LED backlit, 1920x1080 pix                      |
| Built-in Intercom & Tally      | ----   |
| <b>Streaming</b>               |  |
| Streaming                      | H.264: MAX RES 1080p<br>H.265: MAX RES 1080p                 |
| Streaming Audio Encode         | AAC 2CH,<br>16bit 48KHz 192Kbps                              |
| Streaming Protocol             | RTSP<br>RTMP<br>SRT  |
| Streaming Control              | Web browser UI for configuration and control Socket commands |

|                                       |   |
|---------------------------------------|---|
| Recording File System                 | FAT32, exFAT  |
| Recording File Format                 | MP4 (H.265+ AAC) or (H.264+ AAC)  |
| Streaming & Recording Setting Control | Web UI for system configuration and control   |
| <b>Others</b>                         |   |
| Special Features                      | 4 Chroma-Key Virtual Studio<br>9 stinger transition and 4 user preset<br>Built-in CG title overlay system<br>Streaming encoder and recorder |
| Dimension (LxWxH)                     | 455 x 355 x 134 mm  |
| Weight                                | 8.5 kg, Reinforce Plastic Case  |
| Power                                 | DC 12V, 11A   |
| Operating Temp. Range                 | 0~40 °C   |
| What's in the Box                     | 1 x HS-2600 Unit<br>1 x AD Switch DC 12V with AC Cord   |