

Umschalter

4K Zweikanal-Präsentationsumschalter

iCAST mini

Video Standard	4K & HD
Video Format	<p>Input: 3840x2160p: 30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 525i59.94 NTSC, 625i50 PAL</p> <p>Output: HDMI 3840x2160p: 30/29.97/25 1080p: 60/59.94/50/30/29.97/25/24/23.98 UVC 3840x2160p: 30/29.97/25 1080p60/59.94/50/30/29.97/25</p>
Video Processing	4K, 2K/30 4:4:4, 8bit
Input Routable / Crosspoint	N/A
Video Input	2 x HDMI 1.4
Mix HD & SD Source	N/A
Computer Graphic Interface	2 via HDMI
Video Output	1 x HDMI 1.4 1 x USB 3.0 Type C (UVC)
Down-converted Output	Yes
Built-in Multi-view Monitoring Out	N/A
Analogue Audio Input	2 x 3 Pin XLR / 1/4" (6.3mm) Combo Socket
Analogue Audio Output	1 x Stereo RCA set (L/R) 1 x Stereo headphone
Digital Embedded Audio Support	Input 2 channels, Output 2 channels
Audio Delay Calibration	Up to 170ms
A+V Switching	Yes
Chromakey	N/A
Title Creator	N/A
USK	N/A
DSK	N/A
Picture in Picture	1
Logo Insertion	N/A
Still Store	N/A
Effects	Cut
Transition Preview	N/A

Sync / Reference In/Out	N/A
Tally Output	N/A
PC Remote Control	N/A
Camera Control	DVIP/ RS-422/ RS-232
Built-in Audio Mixer	Yes
Storage	N/A
Recording File System	N/A
Recording File Format	N/A
Video Encode	N/A
Audio Encode	N/A
Streaming Protocol	N/A
Firmware Update	USB
Special Features	7" Touchscreen Display
Chassis	Unibody
Dimension (LxWxH)	220 x 154 x 75mm
Weight	1.1 kg
Power	DC 12V 18.7W
Operating Temp. Range	0~40 °C
What's in the Box	1 x iCast MINI product 1 x AD Switch DC 12V with AC Cord