

Video Decoder

4K HDMI IP Video Decoder**NVD-40**

| | |
|-------------------------------|--|
| Audio/Video Input | Stream Input: RTSP over UDP (Unicast / Multicast) RTSP over TCP RTSP over HTTP SRT (Secure Reliable Transport) caller MPEG-TS over UDP RTMP Pull RTMP Push (Internal Server) UDP raw (Unicast/Multicast) HLS over HTTP MPEG-TS over TCP Pull Supported video sharing websites |
| Audio Output | 2 x RCA(L/R) HDMI embedded audio |
| Video Output | HDMI 2.0 x 1 (Digital) Composite x 1 (Analogue) |
| Network Feature | 1x RJ-45 Female (10/100/1000M Ethernet) DHCP/Static IP |
| Supported Video Resolution | 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98 (H.265 Only) 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC) |
| Supported Decoding Resolution | Up to 2160p60/50 |
| Control | Web browser UI for configuration and control Socket commands |
| Update | Automatic firmware upgrade |
| Power | Input AC 100~240V Switching Adaptor Output DC 12V / 1A |
| Environmental Conditions | Operating temperature: 0~40°C, Storage temperature: -20~60°C |
| Dimension (LxWxH) | 220 x 143 x 42 mm |
| Weight | 1 kg |
| Power | DC 12V, 1A |
| What's in the Box | 1 x NVD-40 product 1 x AD Switch DC 12V 1 x Remote Control |