

Teleprompters

# Portable Conference Teleprompter

## TP-800 MARK II

Device Used	15" monitor with integrated dvPrompter Plus software
Camera-Mount Interface	N/A
Smartphone / Tablet Size	N/A
Multi-language Support	English Dutch Spanish Portuguese Russian Chinese(Traditional) Chinese (Simplified)
Hood Dimension / Prompter Size	Width: 410mm Height: 2000mm Depth: 430mm Support bar height range: 45 - 161 cm
LCD Native Resolution	1024x768
LCD Brightness	350 NIT
Remote Control	* Monitoring and control via LAN *Optional WR-500 wired hardware remote
Weight	7.8Kg
Operating Temp. Range	0~40 °C
Power	12V DC (Mains adapter supplied) V-Lock battery PoE (optional adapter required)
Carry Case Dimensions (excluding handle)	H 375mm x W 430mm x D 165mm
What's in the Box	1 x Main TP-800 MARK II ENG hard case & chassis 1 x 15" LCD control unit 1 x Extendable pole with 3/8 screw 1 x Adjustable beam splitter glass clamp 1 x Thumb screw for beam splitter clamp (Item D) 1 x 50/50 glass beam splitter 1 x Universal mains PSU (Or local PSU only for Chinese market) 1 x Ethernet cable 5M 1 x 3.5mm input adapter for WR-500 remote control 1 x USB Mouse 1 x Sun Hood 1 x 12V D-Tap cable