

Datavideo Product Compare

<https://datavideo.com/eu/>

| | |
|----------------------------|--|
| Model Number | HS-2850-12 |
| Product | HD/SD 12-Channel Portable Video Studio |
| Video Standard | HD & SD |
| Video Format | 1080p 25/29/30/50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz |
| Input Rutable / Crosspoint | All 12, repeatable |
| Video Input | Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI |
| Computer Graphic Interface | Max 3 via HDMI |
| Down-converted Output | 3x SDI |
| Video Output | 3x SDI assignable: PGM, PVW, AUX & Clean Out 1x HDMI assignable: PGM & multi-view |
| Analogue Audio Input | 4x Balanced XLR |

| | |
|--------------------------------|---|
| Analogue Audio Output | 2x Balanced XLR |
| Digital Embedded Audio Support | Input up to 16 channels, Output 4 channels |
| Audio Delay Calibration | Up to 8 frames |
| A+V Switching | Yes |
| USK | ---- |
| DSK | 2, support Lumakey & Linear key (Key / Fill) |
| Picture in Picture | 2 |
| Logo Insertion | 2 (or 1 logo + 1 clock) |
| Title Creator | Yes, CG-200 software free download |
| Built-in Audio Mixer | ---- |
| Built-in Monitor Display | 17.3" HD TFT LED backlit, 1600x900 pix |
| Built-in Intercom & Tally | 8 channels (4 belt-packs incl.) |
| Streaming | |
| Streaming | ---- |
| Streaming Audio Encode | ---- |
| Streaming Protocol | ---- |

| | |
|---------------------------------------|---|
| Streaming Control | ---- |
| Recording File System | ---- |
| Recording File Format | ---- |
| Streaming & Recording Setting Control | ---- |
| Others | |
| Special Features | Built in TC-200 CG interface |
| Dimension (LxWxH) | 455 x 355 x 134 mm |
| Weight | 18.7 Lbs (8.5 kg), Reinforce Plastic Case |
| Power | DC 12V, 6A |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | <ul style="list-style-type: none"> 1 x HS-2850 Unit 1 x AD Switch DC 12V with AC Cord 1 x CB-41 / XLR to XLR Cable 4 x CB-3 / XLR cable 1 x Goose neck MIC 4 x Headphone Microphone 4 x ITC-100SL 1 x Tally light 4 x Velcro |