

Datavideo Product Compare

<https://datavideo.com./eu/>

| | |
|-----------------------------|--|
| Model Number | TLM-700UHD |
| Product | 7" 4K LCD Monitor |
| Screen | 7" TFT LCD |
| Chassis | Camera Mount |
| Resolution | 1920x1200 |
| Viewing Angle | (H) +85/-85° (V) +85/-85° |
| Luminance/ Contrast | 450cd/m ² 1000:1 |
| Video Inputs | 1x HDMI (2.0), HDCP 2.2 |
| Loop Through | 1x HDMI (2.0) |
| Supported Input Resolutions | 4096x2160p (23.98/24/25/29.97/30/50/59.94/60Hz) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60Hz) 2048x1080p (50/59.94/60Hz) 1080p (23.98/24/25/29.97/30/50/59.94/60Hz)50i/59.94i/60i) 1080i (50/59.94/60Hz) 720p (23.98/24/25/29.97/30/50/59.94/60Hz) 576i(50Hz), 576p(50Hz), 480i(59.94/60Hz), 480p(59.94/60Hz) |
| Aspect Ratio | Full/16:9/1.85:1/2.35:1/4:3/3:2 |
| Aspect Marker | Off/16:9/1.85:1/2.35:1/4:3/3:2/9:16 |
| Safty Marker | Off/95%/93%/90%/88%/85%/80% |

| | |
|-----------------------|--|
| Tally LED | ---- |
| Audio In/Out | Embedded Audio (48KHz sampling) Analog Stereo (Phone Jack), Speaker x1 (2W) |
| Special Features | Focus assist (peaking), False Color, Histogram, Exposure, Pixel to Pixel Zoom, Underscan, Check Field (blue-only mode, monochrome mode) |
| Dimension (WxHxD) | 182 x 129 x 37 mm |
| Weight | 0.3 kg |
| Operating Temp. Range | 0~40 °C |
| Power | DC 12V, 12W |
| What's in the Box | 1 x TLM-700UHD product 1 x AD Switch DC 12V 1 x Folding sun shade cover 1 x HDMI A/C cable 1 x Battery plate 1 x Hot shoe mount |