

Tête inclinable robotique

Tête panoramique inclinable robotisée 4K HDBaseT**PTR-15T**

| | |
|--------------------------|---|
| Video Interface | HDMI 2.0 x 1 12G-SDI x 1 3G-SDI x 1 RJ45 x 1 (HDBaseT) |
| Video Output | 2160p 60/59.94/50 2160p 30/29.97/25 1080p 60/59.94/50 1080p 30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50 |
| Control Unit | RMC-180 MARK II RMC-300A RMC-300C SHOWCAST 100 VISCA Protocol Controller IP Control IR remote |
| Genlock | YES |
| Timecode | YES |
| Panning / Tilting Range | Pan: 340° Tilt: ±45° |
| Panning / Tilting Speed | Pan: 0.12~15° /Sec Tilt: 0.06~10° /Sec |
| Preset | Pan/Tilt position 199 |
| Control Distance | 1,200M by RS422 100M by DVIP |
| Control Protocol | Sony VISCA DVIP |
| Control Input | RS-422 HDBaseT |
| Maximum Load | 4 KG Max |
| Control Output | RS-232 RS-422 IP Control BX-Lens LanC |
| Power Requirement | DC 14V~ 20V, 90W |
| Power Supply | DC 24/12V, 36W Max |
| Operating Temp. Range | 0~40 C° |
| Operating Humidity Range | 10~80% |
| Storage Temp. Range | -10~60C° |
| Storage Humidity Range | 5~80% |
| Weight | 3.7 kg |

| | |
|----------------------|---|
| Dimension (LxWxH) | 241 x 191 x 300 mm |
| Optional accessories | ZEK-1 ZEK-2 PCB-1 WM-10 WM-11 CM-10 HBT-18 |
| What's in the Box | PTR-15T Main Unit x 1 DC 19V power adaptor x 1 AC cord x 1 IR remote control x 1 DC with lock to D-Tap cable x 1 HDMI cable x 1 SDI cable x 1 Remote cable (2.5mm phone-jack to mini-din 8pin) x 1 1/4" screw x 2 1/4" to 3/8" screw adaptor x 1 |