

# Datavideo Product Compare

<https://datavideo.com./fr/>

Numéro de modèle	<b>HS-2850-8</b>
Product	<b>Studio vidéo portable HD/SD 8 canaux</b>
Video Standard	HD & SD
Video Format	1080p 25/29/30/50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz
Input Rutable / Crosspoint	All 12, repeatable
Video Input	Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI
Computer Graphic Interface	Max 3 via HDMI
Down-converted Output	3x SDI
Video Output	3x SDI assignable: PGM, PVW, AUX & Clean Out 1x HDMI assignable: PGM & multi-view
Analogue Audio Input	4x Balanced XLR

Analogue Audio Output	2x Balanced XLR
Digital Embedded Audio Support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	Up to 8 frames
A+V Switching	Yes
USK	----
DSK	2, support Lumakey & Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Title Creator	Yes, CG-200 software free download
Built-in Audio Mixer	----
Built-in Monitor Display	17.3" HD TFT LED backlit, 1600x900 pix
Built-in Intercom & Tally	8 channels (4 belt-packs incl.)
<b>Streaming</b>	
Streaming	----
Streaming Audio Encode	----
Streaming Protocol	----

Streaming Control	----
Recording File System	----
Recording File Format	----
Streaming & Recording Setting Control	----
<b>Others</b>	
Special Features	Built in TC-200 CG interface
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	18.7 Lbs (8.5 kg), Reinforce Plastic Case
Power	DC 12V, 6A
Operating Temp. Range	0~40 °C
What's in the Box	<ul style="list-style-type: none"> <li>1 x HS-2850 Unit</li> <li>1 x AD Switch DC 12V with AC Cord</li> <li>1 x CB-41 / XLR to XLR Cable</li> <li>4 x CB-3 / XLR cable</li> <li>1 x Goose neck MIC</li> <li>4 x Headphone Microphone</li> <li>4 x ITC-100SL</li> <li>1 x Tally light</li> <li>4 x Velcro</li> </ul>