

Mobile Cast

HD 8-Channel Portable Video Streaming Studio

HS-2600

| | |
|--------------------------------|--|
| Video Standard | HD |
| Video Format | 1080p 50/ 59.94/ 60Hz 1080i 50/ 59.94/ 60Hz 720p 50/ 59.94/ 60Hz |
| Input Rutable / Crosspoint | All 8, repeatable |
| Video Input | 4 x 3G-SDI 4 x HDMI |
| Computer Graphic Interface | 4 via HDMI |
| Down-converted Output | ---- |
| Video Output | 3 x 3G-SDI for PGM (AUX assignable) 1 x HDMI 1.4 for PGM (AUX assignable) 3 x HDMI 1.4 for PGM |
| Analogue Audio Input | 2 x XLR/MIC (6.3mm) Combo Socket 1 x stereo RCA audio |
| Analogue Audio Output | 1 x stereo RCA audio |
| Digital Embedded Audio Support | SDI Input/Output 4 channels, HDMI Input/Output 2 channels |
| Audio Delay Calibration | Up to 16 frames |
| A+V Switching | Yes |
| USK | 4 |
| DSK | 2 |
| Picture in Picture | 4 |
| Logo Insertion | 2 |
| Title Creator | Yes |
| Built-in Audio Mixer | ---- |
| Built-in Monitor Display | 17.3" HD TFT LED backlit, 1920x1080 pix |
| Built-in Intercom & Tally | ---- |

Streaming

| | |
|------------------------|--|
| Streaming | H.264: MAX RES 1080p H.265: MAX RES 1080p |
| Streaming Audio Encode | AAC 2CH, 16bit 48KHz 192Kbps |
| Streaming Protocol | RTSP RTMP SRT |
| Streaming Control | Web browser UI for configuration and control Socket commands |
| Recording File System | FAT32, exFAT |

| | |
|---------------------------------------|---|
| Recording File Format | MP4 (H.265+ AAC) or (H.264+ AAC) |
| Streaming & Recording Setting Control | Web UI for system configuration and control |

Others

| | |
|-----------------------|---|
| Special Features | 4 Chroma-Key Virtual Studio 9 stinger transition and 4 user preset Built-in CG title overlay system Streaming encoder and recorder |
| Dimension (LxWxH) | 455 x 355 x 134 mm |
| Weight | 8.5 kg, Reinforce Plastic Case |
| Power | DC 12V, 11A |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x HS-2600 Unit 1 x AD Switch DC 12V with AC Cord |