

手提式導播室

**HD 6通道手提式移動錄播導播室****HS-1300**

影像系統	HD
影像格式	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
輸入格式設定	All 6, repeatable
影像輸入	4x HD-SDI 2x HDMI
電腦輸入	2 via HDMI
下變換轉換器	----
影像輸出	3x HDMI + 2x SDI assignable: AUX 1-6, PGM, PVW, PGM Clean or Multiview
聲音輸入	2x Balanced XLR
聲音輸出	1x Stereo headphone
聲音嵌入	Input 2 channels, Output 2 channels
聲音延遲	----
聲音同步切換	Yes
USK	2x USK support Chromakey
DSK	2, support Lumakey & Linear key (Key / Fill)
子母畫面	1
LOGO	----
字幕機	----
混音機	----
監看螢幕	17.3" HD TFT LED backlit, 1600x900 pix
通話系統	----

**Streaming**

串流影片編碼	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
串流聲音編碼	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
串流協議	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT
串流控制	Web browser UI for configuration and control Socket commands
錄製檔案系統	FAT, exFAT, NTFS

錄製檔案格式	MP4
錄製設定控制	Web UI for system configuration and control

## Others

特別功能	Streaming encoder and recorder 2 chromakey virtual studio 9 stinger transition and 30 virtual sets included
尺寸	455 x 355 x 134 mm
重量	16.3 Lbs (7.4 kg), Reinforce Plastic Case
電源	DC 12V, 5A
操作溫度	0~40 °C
附件	1 x HS-1300 Product 1 x AD Switch DC 12V with AC Cord