

導播通話系統

導播通話系統**ITC-100**

Tally 接口	2 x 15 Pin DSub Sockets for Tally A and B
耳機麥克風接口	3.5 mm Stereo Jack Socket for Headphone / Microphone combination Headset Impedance 8-600 Ohms 100 mW (min)
耳機接口	¼" (6.3mm) Stereo Headphone Socket Headset Impedance 8-600 Ohms 100 mW (min)
燈光接口 (DC 12V)	3 PIN XLR Connector PIN 2: 12V PIN 3: GND Light Power Consumption: 12 V / 100 mA (MAX.)
麥克風接口	3 PIN XLR / ¼" (6.3mm) Jack Microphone Socket Switchable Condenser / Dynamic Input Microphone Level -67 dB
頻率響應	550-3.6 kHz, <+/- 3dB
總諧波失真(THD)	< 3%
訊號雜訊比(S/N)	> 50dB
內建麥克風	70mm x 30mm 32 Ohm 3 Watts
操作範圍	Up to 200 meters between base station and slave
操作溫度	0~40 °C
尺寸	482 x 127 x 46 mm
重量	1.9 kg
電源	DC 12V, 8W
附件	1 x ITC-100 Base Unit 4 x ITC-100SL Belt Pack 4 x ITC-100SL Carry Case 4 x Cable 5pin XLR to XLR 4 x 3.5mm Jack to 3.5mm Jack Cable 4 x Headset with microphone 4 x Tally LED Indicator 1 x XLR Gooseneck Microphone 1 x XLR Gooseneck Light 1 x 12V 1A Power Supply Unit