

4K 多攝像機切換導播機

4K 影像截取處理器**KMU-100**

影像標準	UHD & HD
影像輸出	3840x2160p 23.98/24/25/29.97/30/50/59.94/60 1080p 23.98/24/25/29.97/30 1080i 50/59.94/60 1080PsF 23.98/24/25/29.97/30 720p 50/59.94/60
影像處理	---
影像輸入	2 sets of SDI Input: each set of 4x SDI 1 x 3Gb/s or 12Gb/s SD/HD/4K. Supports single link 4:2:2 3 x 3Gb/s SD/HD/4K. Supports single link, dual link, and quad link 4:2:2 2 x HDMI Input: each of HDMI support for Ultra HD 4K 60p in 4:2:0/4:2:2
影像輸出	2 sets of SDI output: each set of 4x SDI 1 x 3Gb/s or 12Gb/s SD/HD/4K. Supports single link 4:2:2 3 x 3Gb/s SD/HD/4K. Supports single link, dual link, and quad link 4:2:2
支援輸出影像解析度	1080p 25/29.97/30/50/59.94/60 1080i 50/59.94/60 720p 50/59.94/60 625/50i PAL, 525/59.94i NTSC
多分割畫面輸出	HDMI 1.4 x2
多分割畫面模式	Preview, Motion, Quad

Streaming

直播編碼格式	---
直播影像碼流	---
直播影像解析度模式	---
直播聲音模式	---
直播聲音碼流	---
直播串流協議	---
網路接口	---

Recording

儲存方式	---

錄影檔案格式	---
內建混音器	---

Audio

聲音輸入	SDI: 16 Ch embedded in HD/4K. 8 Ch embedded in SD HDMI: 8 Ch embedded in SD, HD and Ultra HD 4K
聲音輸出	SDI: 16 Ch embedded in HD/4K. 8 Ch embedded in SD HDMI: 8 Ch embedded in SD, HD and Ultra HD 4K
聲音取樣	Television standard sample rate of 48 kHz at 24-bit
同步訊號輸入	Blackburst, Tri-level

Others

控制端子	Ethernet RJ45 for control, configuration and updates RS-232 x 1 input for controlling configuration RS-422 x 1 input with external keyboard support GPIO x1
監看螢幕	---
控制器	RMC-185/RMC-185+
尺寸	484 x 192 x 49 mm
重量	3.2 kg
電源	DC 12V, 5A
操作溫度	0~40 °C
附件	1 x KMU-100 Main Unit 1 x AD Switch DC 12V with AC Cord 4 x Screw