

Datavideo Product Compare

<https://datavideo.com/hk/>

型號	HS-3200
產品	HD 12通道手提式移動錄播導播室
影像系統	Full HD
影像格式	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz
輸入格式設定	All 12, repeatable
影像輸入	8x SDI, 4x HDMI
電腦輸入	4 via HDMI
下變換轉換器	1x SDI
影像輸出	5x SDI, 1x HDMI assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12, STILL 1, STILL 2, Flex source 3x HDMI PGM only
聲音輸入	4x Balanced XLR
聲音輸出	2x Balanced XLR
聲音嵌入	Input 2 channels, Output 4 channels
聲音延遲	Up to 16 frames
聲音同步切換	Yes
USK	4
DSK	2, support Lumakey & Linear key (Key / Fill)
子母畫面	8 (4x Keyer, 4x Flex Source)

LOGO	2
字幕機	Yes, free software download
混音機	----
監看螢幕	17.3" HD TFT LED backlit, 1920x1080 pix
通話系統	----
Streaming	
串流影片編碼	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
串流聲音編碼	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
串流協議	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT
串流控制	Web browser UI for configuration and control Socket commands
錄製檔案系統	FAT, exFAT, NTFS
錄製檔案格式	MP4
錄製設定控制	Web UI for system configuration and control
Others	
特別功能	4 Chroma-Key Virtual Studio 9 stinger transition and 4 user preset Built in TC-200 CG interface Streaming encoder and recorder 12x9 matrix seamless switch
尺寸	455 x 355 x 134 mm
重量	17.8 Lbs (8.1 kg), Reinforce Plastic Case
電源	DC 12V, 11A

操作温度	0~40 °C
附件	1 x HS-3200 Unit 1 x AD Switch DC 12V with AC Cord