

Datavideo Product Compare

<https://datavideo.com/hk/>

型號	PTC-600
產品	4K AI 雲台攝影機
影像格式	Standard/HDBaseT Version: HDMI: 2160p60/59.94/50/30/29.97/25 (2160p60/59.94/50 YUV 4:2:2) 1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50 SDI: 1080p 60/59.94/50/30/29.97/25 720p 60/59.94/50 12G-SDI Version: HDMI/12G-SDI: 2160p60/59.94/50/30/29.97/25 (2160p60/59.94/50 YUV 4:2:2) 1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50 SDI: 1080p 60/59.94/50/30/29.97/25 720p 60/59.94/50
感光元件	1/1.8" CMOS
有效畫素	8.42 Mega Pixels
信噪比	≥55dB
最小明亮度	0.5 Lux @ (F1.8, AGC ON)
電子快門	1/30s ~ 1/10000s
鏡頭倍率	30x Optical, 4x Digital Zoom

Gamma	Off/Normal
光圈設定	Auto/Manual
數位降噪	2D/3D
選單使用語言	English/Simplified Chinese/Traditional Chinese
白平衡	Auto, Indoor, Outdoor, One Push, Manual
ACG/增益控制	Yes
HDR/WDR	N/A
鏡頭翻轉	Yes
對焦模式	Auto/Manual/One Push
水平/垂直範圍	Pan: 340 Tilt: -20~+105
水平/垂直移動速度	
預設點	255 Positions
焦距	30x, f=6.91mm~214.64mm, F1.35(Wide) ~F4.6 (Tele)
視角	60°
圖像補償	Back light compensation

影像輸出	<p>Standard Version: HDMI 2.0 x 1 3G-SDI x1 10/100/1000M RJ45 (802.3at, PoE+) x1 UVC out (USB type C) x1</p> <p>HDBaseT Version: HDMI 2.0 x 1 3G-SDI x1 10/100/1000M RJ45 (802.3at, PoE+) x1 HDBaseT x1 UVC out (USB type C) x1</p> <p>12G-SDI Version: HDMI 2.0 x 1 3G-SDI x1 12G-SDI x1 10/100/1000M RJ45 (802.3at, PoE+) x1 UVC out (USB type C) x1</p>
聲音輸入	XLRx2 (line in), 3.5mm x1 (mic in)
Tally燈	Yes
濾片或廣角鏡	N/A
Protocol	Pelco-D, Pelco-P, VISCA, VISCA over IP, DVIP, ONVIF, NDI
遠端控制端子	<p>Standard/12G-SDI Version: IR, Web GUI, RS-422/RS-232, DVIP, NDI</p> <p>HDBaseT Version: IR, Web GUI, RS-422/RS-232, DVIP, NDI, HDBaseT(RJ-45)</p>
影像壓縮格式	H.264/H.265/MJPEG
聲音壓縮格式	AAC
聲音比特率	96Kbps, 128Kbps, 256Kbps
HD IP Interface	----
串流協議	RTSP, RTMP(S), ONVIF, Multicast, SRT, NDI Hx3

第一串流直 播解析度	3840x2160 1920x1080 1280x720 1024x576 960x540 640x480 640x360
第二串流直 播解析度	1280x720 1024x576 720x576 (50Hz) 720x480 (60Hz) 720x408 640x360 480x270 320x240
影像比特率	32Kbps ~ 50Mbps (Single Stream)
影像比特率 模式	VBR, CBR
編碼 Frame rate	50Hz: 1-50fps 60Hz: 1-60fps
POE	
韌體更新	Via Web UI or USB 3.0 (type C)
IR控制	Yes
攝影機控制 器	RMC-2P RMC-180 series/ RMC-300 series/ PTZ View Assist APP
腳架用螺絲 尺寸	1/4-20 UNC
可用附件	
顏色	Dark Blue/White
尺寸	187(W)x 253(H)x233(D) mm
重量	3.0 kg
操作溫度	0~40 °C

電源	DC 12V
附件	