

LCD Monitors

**4K Dual 10" Monitor****TLM-102K**

|                             |   |
|-----------------------------|---|
| Screen                      | Dual 10.1" LCD  |
| Chassis                     | 4RU Rack Mount  |
| Resolution                  | 1920 × 1200   |
| Viewing Angle               | (H) +85/-85°<br>(V) +85/-85°  |
| Luminance/Contrast          | 1000cd/m <sup>2</sup><br>1000:1   |
| Video Inputs                | 2x 12G-SDI<br>2x HDMI (2.0)   |
| Loop Through                | 2x 12G-SDI<br>2x HDMI (2.0)   |
| Supported Input Resolutions | 4096x2160p 60/59.94/50/30/29.97/25/24/23.98<br>3840x2160p 60/59.94/50/30/29.97/25/24/23.98<br>1920x1080p 60/59.94/50/30/29.97/25/24/23.98<br>1920x1080Psf 30/29.97/25/24/23.98<br>1920x1080i 60/59.94/50<br>1280×720p 60/59.94/50/30/29.97/25/24/23.98<br>720x525i 59.94, 720x625i 50 |
| Aspect Ratio                | 16:10   |
| Aspect Marker               | YES   |
| Safety Marker               | YES   |
| Tally LED                   | Live (Red)<br>Cued (Green)  |
| Audio In/Out                | Embedded Audio (48KHz sampling)<br>Analog stereo (Phone Jack)   |
| Special Features            | time code, audio level meter , peaking, zoom, pix to pix, underscan   |
| Dimension (WxHxD)           | 482 x 178 x 38 mm   |
| Weight                      | 3.6 kg  |
| Operating Temp. Range       | 0~40 °C   |
| Power                       | DC 12V, 28W   |
| What's in the Box           | 1 x TLM-102K product<br>1 x AD Switch DC 12V with AC Cord<br>1 x Tally Convertor<br>2 x Screw $\phi$ 3.0*6m/m<br>4 x Screw M5 x 10mm  |