

# Datavideo Product Compare

<https://datavideo.com./in/>

Model Number	<b>HS-2200</b>
Product	<b>HD 6-Channel Portable Mobile Cast Video Studio</b>
Video Standard	HD & SD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz
Input Rutable / Crosspoint	All 6, repeatable
Video Input	6x HD-SDI, 2x HDMI (on CH5 & 6)
Computer Graphic Interface	2 via HDMI
Down-converted Output	----
Video Output	5x SDI Outputs assignable: AUX 1-4, PGM, PVW, PGM Clean or multiview 1x HDMI assignable: PGM or multi-view
Analogue Audio Input	4x Balanced XLR

Analogue Audio Output	2x Balanced XLR
Digital Embedded Audio Support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	----
A+V Switching	Yes
USK	----
DSK	1, support Lumakey & Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Title Creator	Yes, CG-200 software free download
Built-in Audio Mixer	----
Built-in Monitor Display	
Built-in Intercom & Tally	8 channels (4 belt-packs incl.)
<b>Streaming</b>	
Streaming	----
Streaming Audio Encode	----
Streaming Protocol	----

Streaming Control	----
Recording File System	----
Recording File Format	----
Streaming & Recording Setting Control	----
<b>Others</b>	
Special Features	Built in TC-200 CG interface 6x6 matrix seamless switch
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	16.5 Lbs (7.5 kg), Reinforce Plastic Case
Power	DC 12V, 5A
Operating Temp. Range	0~40 °C
What's in the Box	1 x HS-2200 Unit 1 x AD Switch DC 12V with AC Cord 1 x CB-41 / XLR to XLR Cable 4 x CB-3 / XLR cable 1 x Goose neck MIC 4 x Headphone Microphone 4 x ITC-100SL 1 x Tally light 4 x Velcro