

# Datavideo Product Compare

<https://datavideo.com./in/>

|                                  |  |
|----------------------------------|--|
| Model Number                     | <b>NVS-35</b>  |
| Product                          | <b>H.264 Dual Streaming Encoder</b>  |
| Video Input                      | HDMI x1<br>SDI x1  |
| Supported Video Input Resolution | 1080p 60/59.94/50<br>1080p 30/29.97/25/24/23.98<br>1080i 60/59.94/50<br>720p 60/59.94/50<br>480i 59.94, 576i 50  |
| Video Output                     | Support Down Scaling to 128x128  |
| Audio Input                      | 1 x HDMI embedded audio<br>(Audio depends on the source/ both stereo and mono supported)<br>1 x SDI embedded audio<br>1 x RCA (audio level calibration: +10/+12dB ~ -6dB)<br>2 x XLR (audio level calibration: +10/+12dB ~ -6dB)<br>Mix (Embedded + RCA+XLR) |
| Encode                           | H.264/AVC High Profile Level 4.1   |
| Video Bitrate                    | Record Only: Up to 16Mbps (1080p50/60)<br>Stream Only: Up to 10Mbps (1080p50/60)<br>Rec and Stream: Up to 36Mbps (1080p50/60) (dual stream)  |
| Audio Mode                       | Stereo/Mono  |
| Audio Bitrate                    | AAC-LC<br>Sample rate: 48KHz, 16bit<br>Configurable bit rate: 128K or 256K or 384K   |
| Audio Delay                      |  |

|                       |  |
|-----------------------|--|
| Streaming Protocols   | TS over TCP/UDP (unicast & multicast)<br>RTSP over HTTP/TCP/UDP (RTSP Elementary Stream)<br>RTMP/RTMPS(Publish)<br>SRT |
| Network Interface     |  |
| Recording File Format |  |
| Storage               |  |
| Special Feature       |  |
| Power Supply          |  |
| Dimension (LxWxH)     |  |
| Weight                |  |
| Operating Temp. Range |  |
| What's in the Box     |  |