

# Datavideo Product Compare

<https://datavideo.com./kr/>

|                        |  |
|------------------------|--|
| 모델 넘버                  | <b>HBT-30</b>  |
| 제품                     | 3채널 4K HDBaseT 수신기   |
| Video/Audio Input      | HDBaseT (RJ-45) x 3  |
| Video/Audio Output     | HDMI 2.0 x 3   |
| Supported Video Format | 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98<br>1080p: 60/59.94/50/30/29.97/25/24/23.98<br>1080i: 60/59.94/50<br>720p: 60/59.94/50<br>525i: 59.94 NTSC<br>625i: 50 PAL |
| Video Process          | 4K60 4:4:4, 8bit<br>4K60 4:2:2 10bit<br>4K60 4:2:0 10bit   |
| Video bandwidth        | Single-link 594MHz [18Gbps]  |
| DVIP                   | RJ-45 x1(input)  |
| RS-422/<br>RS-232      | RJ-45 x 3 (RS-232/RS-422)  |
| Power                  | DC IN: DC 56V  |
| PoE Output             | 65W per channel  |
| HDBaseT Distance       | 1080p@60 up to 100M by CAT. 6A cable<br>4K@60 up to 100M by CAT. 6A cable  |
| HDMI compliance        | HDMI Deep Color & 4K@60  |

|                       |   |
|-----------------------|---|
| HDCP compliance       | HDCP 2.2/1.4 (Bypass)   |
| Audio support         | Surround Sound [up to 7.1 Channel) or Stereo Digital Audio      |
| Dimension (LxWxH)     | 440 x 125 x 44.5 mm   |
| Weight                | 1.8Kg   |
| Operating Temp. Range | 0~40 °C   |
| What's in the Box     | 1 x HBT-30 main unit<br>1 x AC cord<br>1 x DC 56V power adaptor |