

Datavideo Product Compare

<https://datavideo.com./kr/>

| | |
|----------------------------|---|
| 모델 넘버 | HS-2200 |
| 제품 | HD 6채널 휴대용 모바일 캐스트 비디오 스튜디오 |
| Video Standard | HD & SD |
| Video Format | 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz |
| Input Rutable / Crosspoint | All 6, repeatable |
| Video Input | 6x HD-SDI, 2x HDMI (on CH5 & 6) |
| Computer Graphic Interface | 2 via HDMI |
| Down-converted Output | ---- |
| Video Output | 5x SDI Outputs assignable: AUX 1-4, PGM, PVW, PGM Clean or multiview 1x HDMI assignable: PGM or multi-view |
| Analogue Audio Input | 4x Balanced XLR |
| Analogue Audio Output | 2x Balanced XLR |

| | |
|--------------------------------|---|
| Digital Embedded Audio Support | Input up to 16 channels, Output 4 channels |
| Audio Delay Calibration | ---- |
| A+V Switching | Yes |
| USK | ---- |
| DSK | 1, support Lumakey & Linear key (Key / Fill) |
| Picture in Picture | 2 |
| Logo Insertion | 2 (or 1 logo + 1 clock) |
| Title Creator | Yes, CG-200 software free download |
| Built-in Audio Mixer | ---- |
| Built-in Monitor Display | |
| Built-in Intercom & Tally | 8 channels (4 belt-packs incl.) |
| Streaming | |
| Streaming | ---- |
| Streaming Audio Encode | ---- |
| Streaming Protocol | ---- |
| Streaming Control | ---- |
| Recording File System | ---- |

| | |
|---------------------------------------|---|
| Recording File Format | ---- |
| Streaming & Recording Setting Control | ---- |
| Others | |
| Special Features | Built in TC-200 CG interface 6x6 matrix seamless switch |
| Dimension (LxWxH) | 455 x 355 x 134 mm |
| Weight | 16.5 Lbs (7.5 kg), Reinforce Plastic Case |
| Power | DC 12V, 5A |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | <ul style="list-style-type: none"> 1 x HS-2200 Unit 1 x AD Switch DC 12V with AC Cord 1 x CB-41 / XLR to XLR Cable 4 x CB-3 / XLR cable 1 x Goose neck MIC 4 x Headphone Microphone 4 x ITC-100SL 1 x Tally light 4 x Velcro |