

Datavideo Product Compare

<https://datavideo.com./kr/>

| | |
|-----------------------------|--|
| 모델 넘버 | SEB-1200 |
| 제품 | SE-1200MU 6채널 스위처 + RMC-260 번들 컨트롤러 |
| Video Standard | HD |
| Video Format | 1080i 50/59.94/60Hz 720p 50/59.94/60Hz |
| Video Processing | SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4 |
| Input Routable / Crosspoint | All 6, repeatable |
| Video Input | 4x HD-SDI 2x HDMI (RGB/YUV, 1080i/1080p/720p) |
| Mix HD & SD Source | ---- |
| Computer Graphic Interface | 2 via HDMI |
| Video Output | 2x HD-SDI 2x HDMI assignable: PGM(w/DSK 1&2), PGM(w/DSK 1), PGM Clean, PVW(w/o DSK), multi-view, Input 1-6 |
| Down-Converted Output | ---- |

| | |
|------------------------------------|---|
| Built-in Multi-view Monitoring Out | HDMI & SDI assignable, Ethernet (MJPEG) |
| Analogue Audio Input | 2x Balanced XLR |
| Analogue Audio Output | ---- |
| Digital Embedded Audio Support | Input 2 channels, Output 2 channels |
| Audio Delay Calibration | ---- |
| A+V Switching | Yes |
| Chromakey | 2 |
| Title Creator | ---- |
| USK | 2x Keyer support Chromakey/ Linear/ Luma Key |
| DSK | 2x DSK support Lumakey/ Linear key (Key / Fill) |
| Picture in Picture | 1 |
| Logo Insertion | ---- |
| Still Store | 500 |
| Effects | FTB, Cut, 32 Wipe with border |
| Transition Preview | Full transitions preview |
| Sync / Reference In/Out | Built-in Genlock (internal) |
| Tally Output | 1x D-sub 15pin, dual color |

| | |
|-----------------------|---|
| PC Remote Control | Ethernet (free Window software) RS-422/ RS-232 |
| Camera Control | |
| Built-in Audio Mixer | ---- |
| Storage | |
| Recording File System | |
| Recording File Format | |
| Video Encode | |
| Audio Encode | |
| Streaming Protocol | |
| Firmware Update | |
| Special Features | Motion JPEG Multi-view streaming (120 memory preset, BGD Transition on/off option) Free Virtual Set and Stinger transition included |
| Chassis | 1RU rack-mount mainframe |
| Dimension (LxWxH) | 440 x 215 x 49 mm (SE-1200MU) 430 x 261 x 70 mm (RMC-260) |
| Weight | 1.5 kg (SE-1200MU) 1.3 kg (RMC-260) |
| Power | DC 12V, 19W (SE-1200MU) DC 12V, 0.5A (RMC-260) |
| Operating Temp. Range | 0~40 °C |

What's in
the Box

SE-1200MU:

1 x SE-1200MU product

1 x AD Switch DC 12V

1 x DB9P TO DB9P Cable

2 x 1U Rack Mount Ear

6 x M4 Screws for Rack Mount Ear

RMC-260:

1 x RMC-260 product

1 x AD Switch DC 12V

1 x DB9P TO DB9P Cable