

# Datavideo Product Compare

<https://datavideo.com/la/>

|                        |  |
|------------------------|--|
| Número de modelo       | <b>ITC-100</b>   |
| Product                | <b>Sistema de Intercom</b>   |
| Tally                  | 2 x 15 Pin DSub Sockets for Tally A and B  |
| MIC / Headset          | 3.5 mm Stereo Jack Socket for Headphone / Microphone combination<br>Headset Impedance 8-600 Ohms 100 mW (min)    |
| Headphone              | ¼" (6.3mm) Stereo Headphone Socket<br>Headset Impedance 8-600 Ohms 100 mW (min)                                  |
| Light Socket (DC 12 V) | 3 PIN XLR Connector<br>PIN 2: 12V<br>PIN 3: GND<br>Light Power Consumption: 12 V / 100 mA (MAX.)                 |
| Microphone             | 3 PIN XLR / ¼" (6.3mm) Jack Microphone Socket<br>Switchable Condenser / Dynamic Input<br>Microphone Level -67 dB |
| Frequency Response     | 550-3.6 kHz, <+/- 3dB  |
| THD                    | < 3%   |
| S/N                    | > 50dB   |
| Built-in Speaker       | 70mm x 30mm 32 Ohm 3 Watts   |
| Operating Range        | Up to 200 meters between base station and slave  |
| Operating Temp. Range  | 0~40 °C  |

|                   |  |
|-------------------|--|
| Dimension (LxWxH) | 482 x 127 x 46 mm  |
| Weight            | 1.9 kg   |
| Power             | DC 12V, 8W   |
| What's in the Box | 1 x ITC-100 Base Unit<br>4 x ITC-100SL Belt Pack<br>4 x ITC-100SL Carry Case<br>4 x Cable 5pin XLR to XLR<br>4 x 3.5mm Jack to 3.5mm Jack Cable<br>4 x Headset with microphone<br>4 x Tally LED Indicator<br>1 x XLR Gooseneck Microphone<br>1 x XLR Gooseneck Light<br>1 x 12V 1A Power Supply Unit |