

# Datavideo Product Compare

<https://datavideo.com./la/>

Número de modelo	<b>NVD-35 MARK II</b>
Product	<b>IP Video Decoder</b>
Audio/Video Input	Stream Input <ul style="list-style-type: none"><li>· RTSP over UDP (Unicast / Multicast)</li><li>· RTSP over TCP</li><li>· RTSP over HTTP</li><li>· SRT (Secure Reliable Transport) caller</li><li>· MPEG-TS over UDP</li><li>· RTMP Pull</li><li>· RTMP Push (Internal Server)</li><li>· UDP raw (Unicast/Multicast)</li><li>· HLS over HTTP</li><li>· MPEG-TS over TCP Pull</li><li>· Video sharing websites</li></ul>
Audio Output	2 x RCA(L/R) SDI embedded audio
Video Output	Composite (analogue) SDI (digital)
Network Feature	1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP
Supported Video Resolution	1080p 60/59.94/30/29.97/25/24 1080i 60/59.94/50 720p 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC)
Supported Decoding Resolution	Up to 1080p60/50

Control	Web browser UI for configuration and control. TCP/IP Socket commands
Update	Automatic firmware upgrade
Power	Input AC 100~240V Switching Adaptor Output DC 12V / 1A
Environmental Conditions	Operating temperature: 0~40°C, Storage temperature: -10~60°C
Dimension (LxWxH)	220 x 143 x 47 mm
Weight	1 kg
Power	DC 12V, 1A
What's in the Box	1 x NVD-35 MARK II product 1 x AD Switch DC 12V 1 x Remote Control