

Видео декодер

IP-видеодекодер 4K HDMI**NVD-40**

Audio/Video Input	Stream Input: RTSP over UDP (Unicast / Multicast) RTSP over TCP RTSP over HTTP SRT (Secure Reliable Transport) caller MPEG-TS over UDP RTMP Pull RTMP Push (Internal Server) UDP raw (Unicast/Multicast) HLS over HTTP MPEG-TS over TCP Pull Supported video sharing websites
Audio Output	2 x RCA(L/R) HDMI embedded audio
Video Output	HDMI 2.0 x 1 (Digital) Composite x 1 (Analogue)
Network Feature	1x RJ-45 Female (10/100/1000M Ethernet) DHCP/Static IP
Supported Video Resolution	3840x2160p: 60/59.94/50/30/29.97/25/24/23.98 (H.265 Only) 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC)
Supported Decoding Resolution	Up to 2160p60/50
Control	Web browser UI for configuration and control Socket commands
Update	Automatic firmware upgrade
Power	Input AC 100~240V Switching Adaptor Output DC 12V / 1A
Environmental Conditions	Operating temperature: 0~40°C, Storage temperature: -20~60°C
Dimension (LxWxH)	220 x 143 x 42 mm
Weight	1 kg
Power	DC 12V, 1A
What's in the Box	1 x NVD-40 product 1 x AD Switch DC 12V 1 x Remote Control