

Видеомикшеры

8-канальный цифровой видеомикшер 4К

SE-4000

| | |
|------------------------------------|--|
| Video Standard | 4K & HD |
| Video Format | <p>Input: 3840x2160p: 60/59.94/50/30/29.97/25 1080p: 60/59.94/50/30/29.97/25 1080i: 60/59.94/50</p> <p>Output: 3840x2160p: 60/59.94/50/30/29.97/25 1080p: 60/59.94/50/30/29.97/25 1080i: 60/59.94/50</p> |
| Video Processing | SDI: 4:2:2 10-bit HDMI: YUV 4:2:2 10-bit, RGB: 4:4:4 8/10-bit |
| Input Routable / Crosspoint | YES |
| Video Input | Total 8 live inputs (select 8 from 12) 8 x 12G-SDI 4 x HDMI |
| Mix HD & SD Source | ---- |
| Computer Graphic Interface | 4 via HDMI |
| Video Output | 4 x 12G-SDI 3 x HDMI All assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12 |
| Down-Converted Output | Yes |
| Built-in Multi-view Monitoring Out | HDMI & SDI assignable |
| Analogue Audio Input | 4 x Analogue XLR |
| Analogue Audio Output | 2 x Analogue XLR |
| Digital Embedded Audio Support | Input 4 channels, Output 4 channels |
| Audio Delay Calibration | Up to 16 fields or 8 frames per channel |
| A+V Switching | Yes |
| Chromakey | 4 |
| Title Creator | Yes (Coming soon by firmware update) |
| USK | 4x Keyer support Chromakey/ Linear/ Luma Key |
| DSK | 2x DSK support Lumakey & Linear key (Key / Fill) |
| Picture in Picture | 2 |
| Logo Insertion | 2 |
| Still Store | 250 |
| Effects | FTB, Cut, 32 Wipe with border |
| Transition Preview | Full transitions preview |

| | |
|-------------------------|--|
| Sync / Reference In/Out | 1 x BNC Ref in 1 x BNC Ref out (loop-through) (available after firmware upgrade) |
| Tally Output | 1x D-sub 25pin, dual color |
| PC Remote Control | DVIP (Ethernet) |
| Camera Control | ---- |
| Built-in Audio Mixer | Yes |
| Storage | ---- |
| Recording File System | ---- |
| Recording File Format | ---- |
| Video Encode | ---- |
| Audio Encode | ---- |
| Streaming Protocol | ---- |
| Firmware Update | USB / Ethernet |
| Special Features | 5" Touchscreen Display |
| Chassis | 2 units, 2RU rack-mount mainframe |
| Dimension (LxWxH) | 433 x 312 x 79 mm (switcher) 432 x 250 x 88 mm (main unit) |
| Weight | 7.1 kg |
| Power | Main Unit: DC 12V, 126W Control Unit: DC 12V 17.3W |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x SE-4000 Main Unit 1 x SE-4000 Control Board 2 x AD Switch DC 12V 1 x AC Cord 1 x Ethernet Cable 12 x Screw 2 x 2U Ear Rack |