

LCD Мониторы

Двойной 10-дюймовый монитор 4К**TLM-102K**

Screen	Dual 10.1" LCD
Chassis	4RU Rack Mount
Resolution	1920 × 1200
Viewing Angle	(H) +85/-85° (V) +85/-85°
Luminance/Contrast	1000cd/m ² 1000:1
Video Inputs	2x 12G-SDI 2x HDMI (2.0)
Loop Through	2x 12G-SDI 2x HDMI (2.0)
Supported Input Resolutions	4096x2160p 60/59.94/50/30/29.97/25/24/23.98 3840x2160p 60/59.94/50/30/29.97/25/24/23.98 1920x1080p 60/59.94/50/30/29.97/25/24/23.98 1920x1080Psf 30/29.97/25/24/23.98 1920x1080i 60/59.94/50 1280×720p 60/59.94/50/30/29.97/25/24/23.98 720x525i 59.94, 720x625i 50
Aspect Ratio	16:10
Aspect Marker	YES
Safety Marker	YES
Tally LED	Live (Red) Cued (Green)
Audio In/Out	Embedded Audio (48KHz sampling) Analog stereo (Phone Jack)
Special Features	time code, audio level meter , peaking, zoom, pix to pix, underscan
Dimension (WxHxD)	482 x 178 x 38 mm
Weight	3.6 kg
Operating Temp. Range	0~40 °C
Power	DC 12V, 28W
What's in the Box	1 x TLM-102K product 1 x AD Switch DC 12V with AC Cord 1 x Tally Convertor 2 x Screw ϕ 3.0*6m/m 4 x Screw M5 x 10mm