

Datavideo Product Compare

<https://datavideo.com./ru/>

| | |
|----------------------------------|--|
| Номер модели | NVS-35 |
| Product | Двухпоточковый кодер H.264 |
| Video Input | HDMI x1 SDI x1 |
| Supported Video Input Resolution | 1080p 60/59.94/50 1080p 30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50 480i 59.94, 576i 50 |
| Video Output | Support Down Scaling to 128x128 |
| Audio Input | 1 x HDMI embedded audio (Audio depends on the source/ both stereo and mono supported) 1 x SDI embedded audio 1 x RCA (audio level calibration: +10/+12dB ~ -6dB) 2 x XLR (audio level calibration: +10/+12dB ~ -6dB) Mix (Embedded + RCA+XLR) |
| Encode | H.264/AVC High Profile Level 4.1 |
| Video Bitrate | Record Only: Up to 16Mbps (1080p50/60) Stream Only: Up to 10Mbps (1080p50/60) Rec and Stream: Up to 36Mbps (1080p50/60) (dual stream) |
| Audio Mode | Stereo/Mono |
| Audio Bitrate | AAC-LC Sample rate: 48KHz, 16bit Configurable bit rate: 128K or 256K or 384K |
| Audio Delay | |

| | |
|-----------------------|--|
| Streaming Protocols | TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Stream) RTMP/RTMPS(Publish) SRT |
| Network Interface | |
| Recording File Format | |
| Storage | |
| Special Feature | |
| Power Supply | |
| Dimension (LxWxH) | |
| Weight | |
| Operating Temp. Range | |
| What's in the Box | |