

# Datavideo Product Compare

<https://datavideo.com.sg/>

|                         |   |
|-------------------------|---|
| Model Number            | <b>PTR-15T</b>  |
| Product                 | <b>4K HDBaseT Robotic Pan Tilt Head</b>   |
| Video Interface         | HDMI 2.0 x 1<br>12G-SDI x 1<br>3G-SDI x 1<br>RJ45 x 1 (HDBaseT)   |
| Video Output            | 2160p 60/59.94/50<br>2160p 30/29.97/25<br>1080p 60/59.94/50<br>1080p 30/29.97/25<br>1080i 60/59.94/50<br>720p 60/59.94/50 |
| Control Unit            | RMC-180 MARK II<br>RMC-300A<br>RMC-300C<br>SHOWCAST 100<br>VISCA Protocol Controller IP Control<br>IR remote              |
| Genlock                 | YES   |
| Timecode                | YES   |
| Panning / Tilting Range | Pan: 340°<br>Tilt: ±45°   |
| Panning / Tilting Speed | Pan: 0.12~15° /Sec<br>Tilt: 0.06~10° /Sec   |
| Preset                  | Pan/Tilt position 199   |

|                          |   |
|--------------------------|---|
| Control Distance         | 1,200M by RS422<br>100M by DVIP                   |
| Control Protocol         | Sony VISCA<br>DVIP                                |
| Control Input            | RS-422<br>HDBaseT                                 |
| Maximum Load             | 4 KG Max  |
| Control Output           | RS-232<br>RS-422<br>IP Control<br>BX-Lens<br>LanC |
| Power Requirement        | DC 14V~ 20V, 90W                                  |
| Power Supply             | DC 24/12V, 36W Max                                |
| Operating Temp. Range    | 0~40 C°   |
| Operating Humidity Range | 10~80%  |
| Storage Temp. Range      | -10~60C°  |
| Storage Humidity Range   | 5~80%   |
| Weight                   | 3.7 kg  |
| Dimension (LxWxH)        | 241 x 191 x 300 mm                                |

|                      |   |
|----------------------|---|
| Optional accessories | ZEK-1<br>ZEK-2<br>PCB-1<br>WM-10<br>WM-11<br>CM-10<br>HBT-18  |
| What's in the Box    | PTR-15T Main Unit x 1<br>DC 19V power adaptor x 1<br>AC cord x 1<br>IR remote control x 1<br>DC with lock to D-Tap cable x 1<br>HDMI cable x 1<br>SDI cable x 1<br>Remote cable (2.5mm phone-jack to mini-din 8pin) x 1<br>1/4" screw x 2<br>1/4" to 3/8" screw adaptor x 1 |