

導播通話系統

**數位導播通話系統****ITC-300**

|               |   |
|---------------|---|
| Tally 接口      | 2 x 15 Pin D-Sub Female Sockets<br>for Tally A and Tally B  |
| 耳機麥克風接口       | 1 x 3.5mm Stereo Jack Socket<br>(For Headphone / Microphone combination)<br>Headset Impedance 24 ohm 100mW(min)<br>Microphone Level -45.2dB<br>(Tip: Mic□Ring: Phone□Sleeve: GND)   |
| 耳機接口          | 1 x 1/4" (6.3mm) Stereo Headphone Socket<br>(Tip: Phone□Ring: Phone□Sleeve: GND)  |
| 燈光接口 (DC 12V) | Light Power Consumption: +5 V / 500 mA  |
| 麥克風接口         | 3 Pin XLR / 1/4" (6.3mm) Socket x 1<br>Switchable Condenser / Dynamic Input<br>Microphone Level -67dB<br>PIN1:N/A,PIN2:MIC,PIN3:GND   |
| 頻率響應          | 300 Hz-7 KHz, < +/-3dB  |
| 總諧波失真(THD)    | < 0.1% @1KHz  |
| 訊號雜訊比(S/N)    | >70dB   |
| 內建麥克風         | 3W<br>Speaker is mute when headphones or mic / headset are connected to the ITC-300   |
| 操作範圍          | Up to 100m between Base Station and Slave   |
| 操作溫度          | 0~40 °C   |
| 尺寸            | 440 x 126 x 44mm  |
| 重量            | 1.9 kg  |
| 電源            | DC 12V, 3A  |
| 附件            | 1 x ITC-300 Base Unit<br>4 x ITC-300SL Belt Pack<br>4 x Ethernet Cable<br>4 x Earphone Cable<br>4 x Headset with microphone<br>1 x Gooseneck Microphone<br>4 x Tally LED Indicator<br>4 x Velcro<br>1 x Adaptor + AC Cord |