

攝影機

4K AI 雲台攝影機**PTC-600**

影像格式	<p>Standard/HDBaseT Version: HDMI: 2160p60/59.94/50/30/29.97/25 (2160p60/59.94/50 YUV 4:2:2) 1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50 SDI: 1080p 60/59.94/50/30/29.97/25 720p 60/59.94/50</p> <p>12G-SDI Version: HDMI/12G-SDI: 2160p60/59.94/50/30/29.97/25 (2160p60/59.94/50 YUV 4:2:2) 1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50 SDI: 1080p 60/59.94/50/30/29.97/25 720p 60/59.94/50</p>
感光元件	1/1.8" CMOS
有效畫素	8.42 Mega Pixels
信噪比	≥55dB
最小明亮度	0.5 Lux @ (F1.8, AGC ON)
電子快門	1/30s ~ 1/10000s
鏡頭倍率	30x Optical, 4x Digital Zoom
Gamma	Off/Normal
光圈設定	Auto/Manual
數位降噪	2D/3D
選單使用語言	English/Simplified Chinese/Traditional Chinese
白平衡	Auto, Indoor, Outdoor, One Push, Manual
ACG/增益控制	Yes
HDR/WDR	N/A
鏡頭翻轉	Yes
對焦模式	Auto/Manual/One Push
水平/垂直範圍	Pan: 340 Tilt: -20~+105
預設點	255 Positions
焦距	30x, f=6.91mm~214.64mm, F1.35(Wide) ~F4.6 (Tele)
視角	60°
圖像補償	Back light compensation

影像輸出	<p>Standard Version: HDMI 2.0 x 1 3G-SDI x1 10/100/1000M RJ45 (802.3at, PoE+) x1 UVC out (USB type C) x1</p> <p>HDBaseT Version: HDMI 2.0 x 1 3G-SDI x1 10/100/1000M RJ45 (802.3at, PoE+) x1 HDBaseT x1 UVC out (USB type C) x1</p> <p>12G-SDI Version: HDMI 2.0 x 1 3G-SDI x1 12G-SDI x1 10/100/1000M RJ45 (802.3at, PoE+) x1 UVC out (USB type C) x1</p>
聲音輸入	XLRx2 (line in), 3.5mm x1 (mic in)
Tally燈	Yes
濾片或廣角鏡	N/A
Protocol	Pelco-D, Pelco-P, VISCA, VISCA over IP, DVIP, ONVIF, NDI
遠端控制端子	<p>Standard/12G-SDI Version: IR, Web GUI, RS-422/RS-232, DVIP, NDI</p> <p>HDBaseT Version: IR, Web GUI, RS-422/RS-232, DVIP, NDI, HDBaseT(RJ-45)</p>
影像壓縮格式	H.264/H.265/MJPEG
聲音壓縮格式	AAC
聲音比特率	96Kbps, 128Kbps, 256Kbps
HD IP Interface	----
串流協議	RTSP, RTMP(S), ONVIF, Multicast, SRT, NDI Hx3
第一串流直播解析度	3840x2160 1920x1080 1280x720 1024x576 960x540 640x480 640x360
第二串流直播解析度	1280x720 1024x576 720x576 (50Hz) 720x480 (60Hz) 720x408 640x360 480x270 320x240
影像比特率	32Kbps ~ 50Mbps (Single Stream)
影像比特率模式	VBR, CBR
編碼 Frame rate	50Hz: 1-50fps 60Hz: 1-60fps

韌體更新	Via Web UI or USB 3.0 (type C)
IR控制	Yes
攝影機控制器	RMC-2P RMC-180 series/ RMC-300 series/ PTZ View Assist APP
腳架用螺絲尺寸	1/4-20 UNC
顏色	Dark Blue/White
尺寸	187(W)x 253(H)x233(D) mm
重量	3.0 kg
操作溫度	0~40 °C
電源	DC 12V