

液晶監視螢幕

4K 17吋向量示波液晶監視螢幕-7U機架式**TLM-170KR**

| | |
|-----------|---|
| 面板 | 17.3" LED Backlit |
| 外觀 | Rack Mount |
| 解析度 | 3840 × 2160 |
| 可視角度 | (H) +89/-89° (V) +89/-89° |
| 亮度/對比 | 300cd/m ² 1000:1 |
| 影像輸入 | 1 x 12G SDI 2 x HDMI (2.0) |
| 環通輸出 | 1 x 12G SDI 1 x HDMI (2.0) |
| 支援影像格式 | SDI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 4096x2160Psf (23.98/24/25/29.97/30) 3840x2160Psf (23.98/24/25/29.97/30) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1920x1080Psf (23.98/24/25/29.97/30) 1280×720p (23.98/24/25/29.97/30/50/59.94/60) 525i, 625i HDMI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1280×720p (23.98/24/25/29.97/30/50/59.94/60) 720 x480i (NTSC), 720 x576i (PAL) 640 x800, 800 x600, 1024 x768, 1280 x800 |
| 長寬比顯示模式 | 16:9, 4:3 |
| 參考線/畫面檢閱器 | YES |
| 安全框 | YES |
| Tally模式 | Live (Red) Cued (Green) |
| 聲音輸入/輸出 | Input: Embedded Audio (48KHz sampling) Output: Analog stereo (Phone Jack) Speaker x 2 (3W) |

| | |
|------|---|
| 特別功能 | waveform, vector scope, Focus Peaking, False Color, Exposure (Zebras), Histogram, HDR / SDR, Time Code, Audio Vector, Camera Log, Gamma, Marker, Pixel to Pixel, Zoom, H/V Delay, DSLR, Freeze, Image Flip, Check Field, Level Meter, Color Bar, Color Calibration. |
| 尺寸 | 403 x 305 x 37 mm |
| 重量 | 5.2kg |
| 操作溫度 | 0~40 °C |
| 電源 | DC 12V, 40.1W |
| 附件 | 1 x TLM-170KR product 1 x AD Switch DC 12V 2 x Rack kit 8 x Screw ϕ 3.0*6m/m 8 x Screw M5 x 10mm 5 x Cable tie |