

Datavideo Product Compare

<https://datavideo.com.tw/>

型號	HS-1600T MARK II
產品	HD/SD 4通道HDBaseT手提式移動錄播導播室
影像系統	HD & SD
影像格式	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i/p 50Hz 480i/p 59.94Hz
輸入格式設定	----
影像輸入	3 x HDBaseT 1 x HDMI
電腦輸入	1 via HDMI
下變換轉換器	Yes
影像輸出	3x HDMI PGM 1x HDBaseT PGM 1x STREAM (RJ-45)
聲音輸入	2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio
聲音輸出	1x Stereo headphone
聲音嵌入	Input 2 channels, Output 2 channels
聲音延遲	----
聲音同步切換	----

USK	1x USK support Lumakey
DSK	----
子母畫面	1
LOGO	----
字幕機	----
混音機	Yes, 4 channels
監看螢幕	17.3" HD TFT LED backlit, 1920x1080 pix
通話系統	----
Streaming	
串流影片編碼	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
串流聲音編碼	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
串流協議	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT
串流控制	Web browser UI for configuration and control Socket commands
錄製檔案系統	FAT, exFAT, NTFS
錄製檔案格式	MP4
錄製設定控制	Web UI for system configuration and control
Others	
特別功能	Built-in camera controller
尺寸	455 x 355 x 134 mm
重量	17.2 Lbs (7.8 kg), Reinforce Plastic Case
电源	DC 48V, 4.16A

操作温度	0~40 °C
附件	1 x HS-1600T MARK II Product 1 x AD Switch DC 56V with AC Cord 3 x Ethernet Cable