

Datavideo Product Compare

<https://datavideo.com.tw/>

| | |
|--------|---|
| 型號 | VGB-4000 |
| 產品 | 4K全媒體錄課系統 |
| 視頻格式 | 3840x2160p 60/59.94/50/30/29.97/25 1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 |
| 視頻輸入 | 1x 12G/6G/3G-SDI 2x HDMI2.0 |
| AUX輸入 | 1x HDMI1.4 (Lumakey Overlay or External Matte or Camera) |
| 視頻輸出 | 2x 12G/6G/3G-SDI 1x HDMI 2.0 |
| 視頻預監輸出 | 1x 12G/6G/3G-SDI 1x HDMI 2.0 1x 12G/6G/3G-SDI Camera loop out |
| 視頻柙像控制 | PC to the RJ-45 |
| 音頻輸入 | 3 x balanced stereo audio / Microphone (3 Pin XLR / 1/4" (6.3mm) Socket) 2 x unbalanced stereo audio, RCA sockets |

| | |
|------------------|--|
| 音频信号规格 | <p>Line Input (XLR): Bandwidth: 20Hz~20KHz < +/- 3dB S/N Ratio: > 80 dB @1KHz, 14dBu (signal level) T.H.D.: < 0.01% @1KHz,14dBu Isolation: > 75dB</p> <p>Line Input (RCA): Bandwidth: 20Hz~20KHz < +/- 3dB S/N Ratio: > 80 dB @1KHz,0dBV (signal level) T.H.D.: < 0.01% @1KHz,0dBV Isolation: > 75dB</p> <p>Mic Input (XLR): Bandwidth: 20Hz~20KHz < +/- 3dB S/N Ratio: > 75 dB @1KHz, +20dB gain > 70 dB @1KHz, +40dB gain T.H.D.: < 0.03% @1KHz, +20dB gain < 0.5% @1KHz, +40dB gain Isolation: > 75dB @+20dB gain > 70dB @+40dB gain</p> |
| 音频延迟 | Up to 3000ms |
| 脚踏开关输入 | 1 x 3 pin mini XLR |
| Streaming | |
| 直播输出 | 1 x RJ-45 (10/100M Ethernet) 1 x USB 2.0 Type A |
| 直播视频编码 | H.264/AVC High Profile Level 4.1 |
| 直播音频编码 | AAC-LC Sample rate: 48KHz, 16bit Configurable bit rate: 128K or 256K or 384K |

| | |
|------------------|---|
| 直播视频分辨率 | 1080p 60/59.94/50 1080p 30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50 480i 59.94, 576i 50 |
| 直播控制协议 | TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Stream) RTMP/RTMPS(Publish) SRT |
| Recording | |
| 录像视频格式 | 2160p 23.98/24/25/29.97/30/50/59.94/60Hz 1080p 23.98/24/25/29.97/30/50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz |
| 录像音频格式 | Uncompressed PCM Sampling rate 24bit 48KHz |
| 录像存储格式 | QuickTime. MOV |
| 录像存储媒介 | 2x 2.5" Removable SSD |
| 录像文件格式 | exFAT |
| 多路录像功能 | Yes, 4-CH HD |
| 色彩取样 / Bit Rate | ProRes 422 HQ ProRes 422 ProRes 422 LT ProRes 422 Proxy |
| 预监屏幕 | 5" Touch LCD |
| Others | |
| 尺寸 | 496 x 460 x 212 mm |
| 重量 | 20 kg |
| 操作温度 | 0~40 °C |

| | |
|----|---|
| 电源 | AC 100-240 VAC DC 12V 400W |
| 附件 | VGB-4000 Main Unit HE-4 (External 2.5" HDD Case) FS-220 Foot Switch VP-840 Unit AC Power Cord SATA to USB3.0 cable |