

Video Decoder

# SDI IP Video Decoder

## NVD-35 MARK II

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio/Video Input             | Stream Input <ul style="list-style-type: none"><li>· RTSP over UDP (Unicast / Multicast)</li><li>· RTSP over TCP</li><li>· RTSP over HTTP</li><li>· SRT (Secure Reliable Transport) caller</li><li>· MPEG-TS over UDP</li><li>· RTMP Pull</li><li>· RTMP Push (Internal Server)</li><li>· UDP raw (Unicast/Multicast)</li><li>· HLS over HTTP</li><li>· MPEG-TS over TCP Pull</li><li>· Video sharing websites</li></ul> |
| Audio Output                  | 2 x RCA(L/R)<br>SDI embedded audio                                                                                                                                                                                                                                                                                                                                                                                       |
| Video Output                  | Composite (analogue)<br>SDI (digital)                                                                                                                                                                                                                                                                                                                                                                                    |
| Network Feature               | 1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP                                                                                                                                                                                                                                                                                                                                                                        |
| Supported Video Resolution    | 1080p 60/59.94/30/29.97/25/24<br>1080i 60/59.94/50<br>720p 60/59.94/50<br>576i 50 (PAL)<br>480i 60 (NTSC)                                                                                                                                                                                                                                                                                                                |
| Supported Decoding Resolution | Up to 1080p60/50                                                                                                                                                                                                                                                                                                                                                                                                         |
| Control                       | Web browser UI for configuration and control.<br>TCP/IP Socket commands                                                                                                                                                                                                                                                                                                                                                  |
| Update                        | Automatic firmware upgrade                                                                                                                                                                                                                                                                                                                                                                                               |
| Power                         | Input AC 100~240V Switching Adaptor<br>Output DC 12V / 1A                                                                                                                                                                                                                                                                                                                                                                |
| Environmental Conditions      | Operating temperature: 0~40°C, Storage temperature: -10~60°C                                                                                                                                                                                                                                                                                                                                                             |
| Dimension (LxWxH)             | 220 x 143 x 47 mm                                                                                                                                                                                                                                                                                                                                                                                                        |
| Weight                        | 1 kg                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Power                         | DC 12V, 1A                                                                                                                                                                                                                                                                                                                                                                                                               |
| What's in the Box             | 1 x NVD-35 MARK II product<br>1 x AD Switch DC 12V<br>1 x Remote Control                                                                                                                                                                                                                                                                                                                                                 |