

LCD Monitors

4K Dual 10" Monitor
TLM-102K

Screen	Dual 10.1" LCD
Chassis	4RU Rack Mount
Resolution	1920 × 1200
Viewing Angle	(H) +85/-85° (V) +85/-85°
Luminance/Contrast	1000cd/m² 1000:1
Video Inputs	2x 12G-SDI 2x HDMI (2.0)
Loop Through	2x 12G-SDI 2x HDMI (2.0)
Supported Input Resolutions	HDMI: 4K60/59.94/50/30/29.97/25/24/23.98 1080P60/59.94/50/30/29.97/25/24/23.98 1080i60/59.94/50, 720p60/59.94/50 480p, 576p SDI: 4K60/59.94/50/30/29.97/25/24/23.98 1080P60/59.94/50/30/29.97/25/24/23.98 1080i60/59.94/50, 720p60/59.94/50 525i59.94 NTSC, 625i50 PAL
Aspect Ratio	16:9, 4:3
Aspect Marker	YES
Safty Marker	YES
Tally LED	Live (Red) Cued (Green)
Audio In/Out	Embedded Audio (48KHz sampling) Analog stereo (Phone Jack)
Special Features	HDR, time code, audio level meter, peaking, zoom, pix to pix, underscan
Dimension (WxHxD)	482 x 178 x 38 mm
Weight	3.6 kg
Operating Temp. Range	0~40 °C
Power	DC 12V, 28W
What's in the Box	1 x TLM-102K product 1 x AD Switch DC 12V with AC Cord 1 x Tally Convertor 2 x Screw ϕ3.0*6m/m 4 x Screw M5 x 10mm

