

Datavideo Product Compare

<https://datavideo.com/af/>

Model Number	GO 650 Studio
Product	4 Channel HD Portable Video Production Studio
Video Standard	HD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB: 4:4:4
Video Input	2x HD-SDI 2x HDMI
Video Output	1x HDMI
Audio Input	1x Stereo RCA (L/R) 2x Mono Microphone De-embedded Digital Audio (2 CH)
Audio Output	1x Stereo RCA (L/R) 1x Stereo headphone (Mini Jack with volume control) Embedded Digital Audio (2 CH)
Embedded Audio Support	Embedded 2-CH digital/analogue audio
ChromaKey	2
USK	1x USK support Chroma Key & Linear/ Luma Key
DSK	1 (Logo)
Picture in Picture	1

Logo Insertion	1
Still Store	500
Effects	FTB, Cut, 32 Wipe with border
Tally Output	1x D-sub 15pin, dual color
Built-in Audio Mixer	Yes
Preview Display	Dual 10.1" LCD
Special Features	Stinger Effect
Streaming	
Streaming Encode	H.264/AVC, Main/High Profile
Streaming Video Bitrate	Record Only: Up to 16Mbps (1080p50/60) Stream Only: Up to 10Mbps (1080p50/60) Rec+Stream: 10Mbps (1080p25/30)
Streaming Audio Mode	Stereo/Mono
Streaming Audio Bitrate	Stereo: 64~384Kbps Mono: 32~192Kbps
Streaming Protocols	TS over TCP/UDP (unicast & multicase) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS
Network Interface	1x RJ45 (10/100Mbps Ethernet)
Streaming Recording File Format	H.264
Streaming Storage	SD Card

Recording	
Recording Storage Medium	SD Card
How to Retrieve Recorded Content	Removable Hard Drive, transfer data via USB 2.0
Recording Storage File System	NTFS, FAT
Recorded File Format	MP4
Audio	
Audio Input	----
Audio Output	----
Audio Indicator	----
Audio Delay	----
Others	
Dimension (LxWxH)	493 x 253 x 331 (monitor's up) 493 x 253 x 190 (monitor's down)
Weight	16 kg
Power	DC 12V, 83W
Operating Temp. Range	0~40 °C

What's in
the Box

- 1 x GO 650 Studio Product
- 1 x AD Switch DC 12V
- 1 x AC Cord
- 3 x HDMI Cable
- 2 x BNC Cable
- 1 x Ethernet Cable
- 10 x Cable Ties