

Estúdio Móvel com

Estúdio portátil de transmissão de vídeo de 8 canais

4K

HS-4000

|                                |                                                                                                                                                         |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Standard                 | 4K & HD                                                                                                                                                 |
| Video Format                   | 3840x2160p: 60/59.94/50/30/29.97/25<br>1080p: 60/59.94/50/30/29.97/25<br>1080i: 60/59.94/50                                                             |
| Input Routable / Crosspoint    | Yes                                                                                                                                                     |
| Video Input                    | Total 8 live inputs (select 8 from 12)<br>8 x 12G-SDI<br>4 x HDMI                                                                                       |
| Computer Graphic Interface     | 4 via HDMI                                                                                                                                              |
| Down-converted Output          | Yes                                                                                                                                                     |
| Video Output                   | 4 x 12G-SDI / 1 x HDMI<br>all assignable :<br>Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12<br>2 x HDMI PGM only<br>1 x HDMI Multiview |
| Analogue Audio Input           | 4x Balanced XLR                                                                                                                                         |
| Analogue Audio Output          | 2x Balanced XLR                                                                                                                                         |
| Digital Embedded Audio Support | Input 4 channels,<br>Output 4 channels                                                                                                                  |
| Audio Delay Calibration        | Up to 16 frames                                                                                                                                         |
| A+V Switching                  | Yes                                                                                                                                                     |
| USK                            | 4                                                                                                                                                       |
| DSK                            | 2, support Luma-key & Linear key<br>(Key / Fill)                                                                                                        |
| Picture in Picture             | 2                                                                                                                                                       |
| Logo Insertion                 | 2                                                                                                                                                       |
| Title Creator                  | Yes (Coming soon by firmware update)                                                                                                                    |
| Built-in Audio Mixer           | Yes                                                                                                                                                     |
| Built-in Monitor Display       | 17.3" 4K TFT LED backlit, 3840x2160 pix                                                                                                                 |
| Built-in Intercom & Tally      | ----                                                                                                                                                    |

Streaming

|                        |                                                                              |
|------------------------|------------------------------------------------------------------------------|
| Streaming              | H.264: MAX RES: HD@60 420 8bit codec<br>H.265: MAX RES: 4K@60 420 8bit codec |
| Streaming Audio Encode | AAC 2CH,<br>16bit 48KHz 192Kbps                                              |
| Streaming Protocol     | RTMP<br>SRT                                                                  |

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Streaming Control                     | Web browser UI for configuration and control Socket commands |
| Recording File System                 | FAT32, exFAT                                                 |
| Recording File Format                 | MP4 (H.265+ AAC) or (H.264+ AAC)                             |
| Streaming & Recording Setting Control | Web UI for system configuration and control                  |

**Others**

|                       |                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------|
| Special Features      | 5" Touch Panel<br>17.3" 4K Monitor<br>4 Chroma-Key Virtual Studio<br>Streaming encoder and recorder |
| Dimension (LxWxH)     | 455 x 370 x 134 mm                                                                                  |
| Weight                | 9.2 kg, Reinforce Plastic Case                                                                      |
| Power                 | DC 56V, 4.46A                                                                                       |
| Operating Temp. Range | 0~40 °C                                                                                             |
| What's in the Box     | 1 x HS-4000 Unit<br>1 x AD Switch DC 48~56V with AC Cord                                            |