

Datavideo Product Compare

<https://datavideo.com/br/>

Número do modelo	HS-1400
Product	Estúdio portátil de streaming de vídeo HD de 5 canais
Video Standard	HD
Video Format	Input: HDMI 3840x2160p: 60/59.94/50/30/29.97/25/24 (HDMI Input 1/2) 1080p: 60/59.94/50/30/29.97/25/24 1080i: 60/59.94/50 720p: 60/59.94/50 Output: 1080p: 60/59.94/50/30/29.97/25/24 1080i: 60/59.94/50
Input Rutable / Crosspoint	All 8, repeatable
Video Input	4 x HDMI (2 x 2.0 + 2 x 1.4a) 4 x 3G-SDI selectable NDI HX2 and media input selectable
Computer Graphic Interface	4 via HDMI
Down-converted Output	-----

Video Output	2x HDMI PGM 1x HDMI for PGM (AUX assignable) 1x SDI for PGM (AUX assignable) 1x USB Type-C (UVC)
Analogue Audio Input	2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio
Analogue Audio Output	1x Stereo headphone
Digital Embedded Audio Support	Input 2 channels, Output 2 channels
Audio Delay Calibration	Up to 1000 ms
A+V Switching	Yes
USK	2x USK support Chromakey and Lumakey
DSK	1
Picture in Picture	2
Logo Insertion	2
Title Creator	---
Built-in Audio Mixer	Yes
Built-in Monitor Display	17.3" HD TFT LED backlit, 1920x1080 pix
Built-in Intercom & Tally	----
Streaming	

Streaming	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 20Mbps
Streaming Audio Encode	AAC 2CH, Sample rate: 48KHz
Streaming Protocol	RTSP RTMP SRT NDI Hx2
Streaming Control	Web browser UI for configuration and control Socket commands
Recording File System	FAT32, exFAT, NTFS
Recording File Format	MP4, TS, FLV
Streaming & Recording Setting Control	Web UI for system configuration and control
Others	
Special Features	Support Media Player via USB, SD Card Support NDI HX2 input
Dimension (LxWxH)	455 x 370 x 134 mm
Weight	7.3 kg, Reinforce Plastic Case
Power	DC 12V, 5A
Operating Temp. Range	0~40 °C
What's in the Box	1 x HS-1400 Unit 1 x AD Switch DC 12V with AC Cord