

4K Virtual Multicam Switcher

4K-Mehrkanal-Touchscreen-Umschalter für „Region of Interest“

KMU-200

|                                 |                                                                                                                                |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Video Standard                  | UHD & HD                                                                                                                       |
| Video Format                    | Input:<br>3840x2160p 23.98/24/25/29.97/30/50/59.94/60<br>1080p 50/59.94/60<br>Output:<br>1080p 50/59.94/60<br>720p 50/59.94/60 |
| Video Format                    | 4:4:4 / 4:2:2 / 4:2:0                                                                                                          |
| Video Input                     | 1x HDMI 2.0<br>1x HDMI 1.4 with Loop through                                                                                   |
| Video Output                    | 2x HDMI 1.4                                                                                                                    |
| Support Video Output Resolution | 1920 x 1080p 50/59.94/60<br>1280 x 720p 50/59.94/60                                                                            |
| Multiview Out                   | ---                                                                                                                            |
| Multiview Mode                  | ---                                                                                                                            |

Streaming

|                           |                                                                                                                                     |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Streaming Encode          | H.264/AVC, Main/High Profile                                                                                                        |
| Streaming Video Bitrate   | Record Only: Up to 16Mbps (1080p50/60)<br>Stream Only: Up to 10Mbps (1080p50/60), dual stream<br>Record+Stream: 36Mbps (1080p50/60) |
| Streaming Video Rate Mode | CBR                                                                                                                                 |
| Streaming Audio Mode      | Stereo/Mono                                                                                                                         |
| Streaming Audio Bitrate   | Stereo: 64~384Kbps<br>Mono: 32~192Kbps                                                                                              |
| Streaming Protocols       | TS over TCP/UDP (unicast & multicast)<br>RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming)<br>RTMP/RTMPS (Publish)<br>HLS<br>SRT   |
| Network Interface         | 1x RJ45 (10/100Mbps Ethernet)                                                                                                       |

Recording

|                               |                          |
|-------------------------------|--------------------------|
| Recording Storage Medium      | SD Card (Class 10 above) |
| Recording Storage File System | NTFS, FAT, exFAT         |
| Recorded File Format          | MP4                      |
| Built-in Audio Mixer          | Yes, 4 channels          |

Audio

|                 |                       |
|-----------------|-----------------------|
| Audio Input     | 2x XLR(Mic)<br>2x RCA |
| Audio Output    | 2x Unbalanced RCA     |
| Audio Sampling  | ---                   |
| Reference Input | ---                   |

Others

|                       |                                                            |
|-----------------------|------------------------------------------------------------|
| Control Interface     | ---                                                        |
| Preview Display       | 14" Capacitive Touch LCD                                   |
| Controller            | ---                                                        |
| Dimension (LxWxH)     | 438 x 331 x 114 mm                                         |
| Weight                | 4.3 kg                                                     |
| Power Supply          | DC 12V, 52W                                                |
| Operating Temp. Range | 0~40 °C                                                    |
| What's in the box     | 1 x KMU-200 Main Unit<br>1 x AD Switch DC 12V with AC Cord |