Video-Decoder

# IP Video Decoder

## NVD-35 MARK II

| | |
|---|---|
| Audio/Video Input | Stream Input<br>· RTSP over UDP (Unicast / Multicast)<br>· RTSP over TCP<br>· RTSP over HTTP<br>· SRT (Secure Reliable Transport) caller<br>· MPEG-TS over UDP<br>· RTMP Pull<br>· RTMP Push (Internal Server)<br>· UDP raw (Unicast/Multicast)<br>· HLS over HTTP<br>· MPEG-TS over TCP Pull<br>· Video sharing websites |
| Audio Output | 2 x RCA(L/R)<br>SDI embedded audio |
| Video Output | Composite (analogue)<br>SDI (digital) |
| Network Feature | 1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP |
| Supported Video Resolution | 1080p 60/59.94/30/29.97/25/24<br>1080i 60/59.94/50<br>720p 60/59.94/50<br>576i 50 (PAL)<br>480i 60 (NTSC) |
| Supported Decoding Resolution | Up to 1080p60/50 |
| Control | Web browser UI for configuration and control.<br>TCP/IP Socket commands |
| Update | Automatic firmware upgrade |
| Power | Input AC 100~240V Switching Adaptor<br>Output DC 12V / 1A |
| Environmental Conditions | Operating temperature: 0~40°C, Storage temperature: -10~60°C |
| Dimension (LxWxH) | 220 x 143 x 47 mm |
| Weight | 1 kg |
| Power | DC 12V, 1A |
| What's in the Box | 1 x NVD-35 MARK II product<br>1 x AD Switch DC 12V<br>1 x Remote Control |