

# Datavideo Product Compare

<https://datavideo.com/de/>

|                        |   |
|------------------------|---|
| Modell-Nr              | <b>TLM-170KR</b>                            |
| Product                | <b>17 Zoll ScopeView Produktionsmonitor</b> |
| Screen                 | 17.3" LED Backlit                           |
| Chassis                | Rack Mount                                  |
| Resolution             | 3840 × 2160                                 |
| Viewing Angle          | (H) +89/-89°<br>(V) +89/-89°                |
| Luminance/<br>Contrast | 300cd/m <sup>2</sup><br>1000:1              |
| Video Inputs           | 1 x 12G SDI<br>2 x HDMI (2.0)               |
| Loop<br>Through        | 1 x 12G SDI<br>1 x HDMI (2.0)               |

|                             |   |
|-----------------------------|---|
| Supported Input Resolutions | SDI:<br>4096x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>3840x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>4096x2160Psf (23.98/24/25/29.97/30)<br>3840x2160Psf (23.98/24/25/29.97/30)<br>1920x1080p (23.98/24/25/29.97/30/50/59.94/60)<br>1920x1080i (50/59.94/60)<br>1920x1080Psf (23.98/24/25/29.97/30)<br>1280x720p (23.98/24/25/29.97/30/50/59.94/60)<br>525i, 625i<br>HDMI:<br>4096x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>3840x2160p (23.98/24/25/29.97/30/50/59.94/60)<br>1920x1080p (23.98/24/25/29.97/30/50/59.94/60)<br>1920x1080i (50/59.94/60)<br>1280x720p (23.98/24/25/29.97/30/50/59.94/60)<br>720 x480i (NTSC), 720 x576i (PAL)<br>640 x800, 800 x600, 1024 x768, 1280 x800 |
| Aspect Ratio                | 16:9, 4:3   |
| Aspect Marker               | YES   |
| Safty Marker                | YES   |
| Tally LED                   | Live (Red)<br>Cued (Green)  |
| Audio In/Out                | Input: Embedded Audio (48KHz sampling)<br>Output: Analog stereo (Phone Jack)<br>Speaker x 2 (3W)  |

|                       |   |
|-----------------------|---|
| Special Features      | waveform,<br>vector scope,<br>Focus Peaking,<br>False Color,<br>Exposure (Zebras),<br>Histogram,<br>HDR / SDR,<br>Time Code,<br>Audio Vector,<br>Camera Log,<br>Gamma, Marker,<br>Pixel to Pixel,<br>Zoom,<br>H/V Delay,<br>DSLR,<br>Freeze,<br>Image Flip,<br>Check Field,<br>Level Meter,<br>Color Bar,<br>Color Calibration. |
| Dimension (WxHxD)     | 403 x 305 x 37 mm   |
| Weight                | 5.2kg   |
| Operating Temp. Range | 0~40 °C   |
| Power                 | DC 12V, 40.1W   |
| What's in the Box     | 1 x TLM-170KR product<br>1 x AD Switch DC 12V<br>2 x Rack kit<br>8 x Screw $\phi$ 3.0*6m/m<br>8 x Screw M5 x 10mm<br>5 x Cable tie  |