

HDBaseT

HDBaseT Transmitter Box**HBT-5**

| | |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Video/Audio Input | HDMI x1 |
| Video/Audio Output | HDBaseT RJ-45 x1 |
| Supported Video Format | 3840x2160p: 30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 525i59.94 NTSC, 625i50 PAL |
| Video Process | 4K2K30 4:4:4 8bit 4K2K60 4:2:0 8bit |
| Video bandwidth | Single-link 340MHz [10.2Gbps] |
| DVIP | --- |
| RS-422/ RS-232 | YES |
| Power | DC Out: 12V 24W |
| PoE Output | --- |
| HDBaseT Distance | 1080p@60 60m (198ft) by CAT6 cable 4K2K@30 35m (114ft) by CAT6 cable |
| HDMI compliance | HDMI Deep Color, full 3D & 4K2K@30 |
| HDCP compliance | HDCP 2.2/1.4 |
| Audio support | Surround sound [up to 7.1ch) or stereo digital audio |
| Dimension (LxWxH) | 88 x 76 x 30 mm |
| Weight | 151 g |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x HBT-5 main unit 1 x DC to DC cable 2 x Screw |