

Teleprompters

# Portable Conference Teleprompter

## TP-800

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device Used                              | 15" monitor with integrated dvPrompter Plus software                                                                                                                                                                                                                                                                                                                                                                                                                |
| Camera-Mount Interface                   | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Smartphone / Tablet Size                 | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Supported Languages                      | Unicode                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Hood Dimension / Prompter Size           | Width: 410mm<br>Height: 2000mm<br>Depth: 430mm<br>Support bar height range: 45 - 161 cm                                                                                                                                                                                                                                                                                                                                                                             |
| LCD Native Resolution                    | 1024x768                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| LCD Brightness                           | 350 NIT                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Remote Control                           | * Monitoring and control via LAN<br>*Optional WR-500 wired hardware remote                                                                                                                                                                                                                                                                                                                                                                                          |
| Weight                                   | 7.8Kg                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Operating Temp. Range                    | 0~40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Power                                    | 12V DC (Mains adapter supplied)<br>V-Lock battery<br>PoE (optional adapter required)                                                                                                                                                                                                                                                                                                                                                                                |
| Carry Case Dimensions (excluding handle) | H 375mm x W 430mm x D 165mm                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| What's in the Box                        | 1 x Main TP-800 ENG hard case & chassis<br>1 x 15" LCD control unit<br>1 x Extendable pole with 3/8 screw<br>1 x Adjustable beam splitter glass clamp<br>1 x Thumb screw for beam splitter clamp (Item D)<br>1 x 50/50 glass beam splitter<br>1 x Universal mains PSU (Or local PSU only for Chinese market)<br>1 x Ethernet cable 5M<br>1 x 3.5mm input adapter for WR-500 remote control<br>1 x USB Mouse<br>1 x Sun Hood<br>1 x 12V D-Tap cable<br>Retail carton |