Datavideo Product Compare

https://datavideo.com/eu/

Model Number	**DAC-70**
Product	**Up / Down / Cross Converter**
Configuration	
Conversion	VGA/HDMI/SDI to HDMI/SDI Multi-format Up/Down/Cross
Video Inputs	1x VGA, 1x HDMI, 1x 3G/HD/SD-SDI (support Level A and Level B)
Loop Through	Yes
Video Outputs	2x 3G/HD/SD-SDI with embedded Audio (support Level A and Level B) 1x HDMI
Audio Inputs	2x RCA (Stereo Pair), 2x SDI/HDMI Audio embedded
Audio Input Impedance	
Audio Outputs	SDI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio up to 8CH, 48KHz, PCM audio
Audio Output Impedance	
Audio Format Selection	----
Audio Gain	----

Supported Video Input Formats	1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080psf(23.98/24/25/29.97/30Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz), 625i, 576p, 576i, 525i, 480p, 480i, 1920x1080(60Hz), 1280x720(60Hz), 1600x1200(60Hz), 1400x1050(60Hz), 1366x768(60Hz), 1280x1024(60Hz), 1024x768(60Hz), 800x600 (60Hz)
Output Resolutions	1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz), 625i, 525i
Equalizer	Yes
Reclock	Yes
SDI Cable Drive	Yes
Updates and Configuratio n	Mini USB x 1
Dimension (LxWxH)	112 x 85 x 45 mm
Weight	0.4 kg
Operating Temp. Range	0~40 °C
Power	DC 12V, 6W
What's in the Box	1 x DAC-70 1 x AD Switch DC 12V 1 x DIP switch Pin 8 label