

Caméras

**Caméra PTZ 4K****PTC-200**

|                                  |                                                                                                                                                                     |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video format/Resolution          | 2160p 29.97/25<br>1080p 59.94/50<br>1080i 59.94/50<br>720p 59.94/50                                                                                                 |
| Image Sensor                     | 1/2.3" type Exmor R CMOS                                                                                                                                            |
| Effective Pixels (approx.)       | 8.93 Mega pixels                                                                                                                                                    |
| S/N Ratio                        | ----                                                                                                                                                                |
| Min. Illumination                | 50%, High Sensitivity Mode:<br>Color: 0.75 lx (F1.8, AGC on, 1/30 sec)<br>50%, Normal Mode:<br>Color: 3 lx (F1.8, AGC on, 1/30 sec)                                 |
| Electronic Shutter               | 1/25 (1/30), 1/50 (1/60), 1/75(1/90), 1/100, 1/120 (1/125), 1/150(1/180),<br>1/215( 1/250), 1/300(1/350), 1/425(1/500), 1/600(1/725), 1/1000,<br>1/1250(1/1500) sec |
| Zoom Ratio                       | 12x Optical Zoom                                                                                                                                                    |
| Gamma Control                    | Off / Normal / Standard Mode 1-4                                                                                                                                    |
| Iris Control                     | Auto / Manual                                                                                                                                                       |
| Digital Noise Reductions         | Yes                                                                                                                                                                 |
| On-Screen Display (OSD)          | English                                                                                                                                                             |
| White Balance                    | Auto, Indoor, Outdoor, Sodium Vapor Lamp, One-push, Manual                                                                                                          |
| AGC / Gain Control               | Auto/Manual (0 dB to 33 dB)<br>Max. Gain Limit (9 dB to 33 dB)                                                                                                      |
| Mirror / Flip Image              | Yes                                                                                                                                                                 |
| Focus Mode                       | Auto (Sensitivity: normal, low), One-push AF, Manual, Zoom Trigger AF                                                                                               |
| Panning / Tilting Range          | Pan: 270° , Tilt: +90° to -17°                                                                                                                                      |
| Panning / Tilting Speed          | Manual: 1~150°/Sec<br>Swing: 1~150°/Sec                                                                                                                             |
| Preset                           | 50 Position                                                                                                                                                         |
| Focal Length                     | f=3.9 mm (wide) to 46.8 mm (tele)                                                                                                                                   |
| Field of View (Horizontal, Wide) | Approx. 70.7° (WIDE END) / 6.4° (TELE END)                                                                                                                          |
| Image Compensation               | Day & Night Function                                                                                                                                                |
| Video Output                     | HDMI x1<br>3G-SDI x1                                                                                                                                                |
| Audio Input                      | ----                                                                                                                                                                |
| Tally LED                        | Dual color (Red, Green)                                                                                                                                             |
| Lens Filter                      | N/A                                                                                                                                                                 |
| Control Protocol                 | VISCA, DVIP                                                                                                                                                         |

|                                    |                                                                                                                                                                                                                                                     |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Remote Control Interface           | RS-422: Transmit up to 1000m<br>DVIP (RJ45): 100m                                                                                                                                                                                                   |
| Video Compression Format           | ----                                                                                                                                                                                                                                                |
| Audio Compression Format           | ----                                                                                                                                                                                                                                                |
| Audio Bitrate                      | ----                                                                                                                                                                                                                                                |
| HD IP Interface                    | ----                                                                                                                                                                                                                                                |
| Streaming Protocols                | ----                                                                                                                                                                                                                                                |
| First Stream Supported Resolution  | ----                                                                                                                                                                                                                                                |
| Second Stream Supported Resolution | ----                                                                                                                                                                                                                                                |
| Video Bitrate                      | ----                                                                                                                                                                                                                                                |
| Video Bitrate Mode                 | ----                                                                                                                                                                                                                                                |
| Encoding Frame rate                | ----                                                                                                                                                                                                                                                |
| POE                                | ----                                                                                                                                                                                                                                                |
| F/W Update                         | USB                                                                                                                                                                                                                                                 |
| IR Control                         | Yes                                                                                                                                                                                                                                                 |
| Camera Control Unit                | RMC-180 series/RMC-300 series                                                                                                                                                                                                                       |
| Tripod Mount                       | 1/4-20 UNC                                                                                                                                                                                                                                          |
| Optional Accessories               | WM-1/ WM-10/ WM-11                                                                                                                                                                                                                                  |
| Color                              | Dark blue                                                                                                                                                                                                                                           |
| Dimension (LxWxH)                  | 173(W)x 189(H) x 219(D)                                                                                                                                                                                                                             |
| Weight                             | 2.8 kg                                                                                                                                                                                                                                              |
| Operating Temp. Range              | 0~40 °C                                                                                                                                                                                                                                             |
| Power                              | DC 12V 31W                                                                                                                                                                                                                                          |
| What's in the Box                  | 1 x PTC-200 Unit<br>1 x IR remote controller<br>1 x PTC-200 Thank You Card<br>1 x Ceiling mount bracket-A<br>1 x Ceiling mount bracket-B<br>6 x Ceiling mount bracket screw M3*4mm<br>1 x DC 12V Power Adaptor<br>1 x Power Cord<br>1 x A tightrope |