

Moniteurs LCD

# 17" ScopeView Production Monitor- Unité de montage en rack 7U

## TLM-170VR

|                             |                                                                                                                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Screen                      | 17.3" LED Backlit                                                                                                                                                                                  |
| Chassis                     | 7RU Rack Mount                                                                                                                                                                                     |
| Resolution                  | 1920x1080                                                                                                                                                                                          |
| Viewing Angle               | (H) +89/-89°<br>(V) +89/-89°                                                                                                                                                                       |
| Luminance/Contrast          | 300cd/m <sup>2</sup><br>700:1                                                                                                                                                                      |
| Video Inputs                | 1x 3G/HD/SD-SDI<br>2x HDMI                                                                                                                                                                         |
| Loop Through                | 1x 3G/HD/SD-SDI                                                                                                                                                                                    |
| Supported Input Resolutions | 1080p(23.98/24/25/29.97/30/50/59.95/60Hz)<br>1080i(50/59.94/60Hz),<br>720p(50/59.94/60Hz),<br>576i(PAL), 480i(NTSC)                                                                                |
| Aspect Ratio                | 16:9, 4:3                                                                                                                                                                                          |
| Aspect Marker               | YES                                                                                                                                                                                                |
| Safty Marker                | YES                                                                                                                                                                                                |
| Tally LED                   | Live (Red)<br>Cued (Green)                                                                                                                                                                         |
| Audio In/Out                | 2x Speaker<br>1x Headphone Jack                                                                                                                                                                    |
| Special Features            | SDI and HDMI cross conversion,<br>Support column (YRGB peak),<br>time code, waveform,<br>vector scope & audio level meter,<br>peaking focus assist,<br>zoom, pix to pix,<br>underscan, check field |
| Dimension (WxHxD)           | 481.8 x 305 x 41 mm                                                                                                                                                                                |
| Weight                      | 4.1 kg                                                                                                                                                                                             |
| Operating Temp. Range       | 0~40 °C                                                                                                                                                                                            |
| Power                       | DC 12V, 21.9W                                                                                                                                                                                      |
| What's in the Box           | 1 x TLM-170V product<br>1 x AD Switch DC 12V<br>2 x Rack kit<br>8 x Screw $\phi$ 3.0*6m/m<br>8 x Screw M5 x 10mm<br>5 x Cable tie                                                                  |